

ALLOY WHEEL REPAIR KIT

MODEL NO: SCS903

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.







instructions

gloves

1. SAFETY

- WARNING! Ensure Health & Safety, local authority and general workshop practice regulations are adhered to when using this product.
- WARNING! Familiarise yourself with the specific applications and limitations of the product as well as any potential hazards.
- WARNING! This kit contains glue. If you require a safety data sheet, contact your Sealey stockist.
- Keep out of reach of children. Store locked away.
- ~ May cause respiratory irritation. Only use outdoors in a well ventilated area.
- ~ Wear protective gloves/protective clothing/eye protection/face protection.
- WARNING! Chemical reaction created by mixing the glue could harm skin.
- WARNING! Avoid contact with skin. IF ON SKIN wash with plenty of soap and water. Release stuck skin with acetone.
- WARNING! Avoid contact with eyes. IF IN EYES rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists get medical advice/attention.
- Keep children, animals and unauthorised persons away from the work area.
- × DO NOT use if you are tired or under the influence of alcohol, drugs or intoxicating medication.

2. INTRODUCTION

Permanently repairs curb damage, scratches, slight dents and sanding marks on alloy, composite and steel rims as well as hubcaps. Kit includes everything required to repair damage simply and quickly.

SPECIFICATION

Model No:	. SCS903
Nett Weight:	. 0.045kg

4. OPERATION

NOTE: This product is not suitable for any type of structural repairs.

- 4.1. Using the sanding paper or file provided, sand and smooth the damaged area.
- 4.1.1. Once the area has been smoothed sufficiently, thoroughly clean and dry it, using the wipes provided.
- 4.2. In equal measures, thoroughly mix the repair adhesive on a smooth clean dry surface using the spatula provided.
- 4.3. Use the spatula provided to apply the adhesive to the damaged area and allow to cure, (10 to 20 minutes dependant on temperature).
- 4.4 Once cured, sand the adhesive down to the required finish.
- 4.5. Apply the silver paint using the brush provided, the paint will fully dry in 1 to 2 hours (dependant on temperature).

Parts support is available for this product. Please log on to www.sealey.co.uk, email sales@sealey.co.uk or telephone 01284 757500



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR 01284 757500 01284 703534 🙊 sales@sealey.co.uk www.sealey.co.uk