

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2021 Version number 58 Revision: 11.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP® BITUMEN UNDERCOATING BLACK BRUSH CAN 1,3 KG
- · Article number: 000016
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC7 Industrial spraying

PROC10 Roller application or brushing

PROC11 Non industrial spraying

- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

Fax: +31 (0)561 694411

e-mail: msds@nl.motipdupli.com

- · Further information obtainable from: Department Product Safety
- 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date 08.02.2021 Version number 58 Revision: 11.03.2020

Trade name: MOTIP® BITUMEN UNDERCOATING BLACK BRUSH CAN 1,3 KG

(Contd. of page 1)

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

· Signal word Warning

· Hazard-determining components of labelling:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C9, aromatics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 919-446-0 Reg.nr.: 01-2119458049-33	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	5-<10%

(Contd. on page 3)

Printing date 08.02.2021 Version number 58 Revision: 11.03.2020

Trade name: MOTIP® BITUMEN UNDERCOATING BLACK BRUSH CAN 1,3 KG

EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	5-<10%
	 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 	
CAS: 67-56-1	methanol	<1%
EINECS: 200-659-6	♦ Flam. Liq. 2, H225	
Index number: 603-001-00-X	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331	
Reg.nr.: 01-2119433307-44	♦ STOT SE 1, H370	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textbf{4.3 Indication of any immediate medical attention and special treatment needed}$

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 08.02.2021 Version number 58 Revision: 11.03.2020

Trade name: MOTIP® BITUMEN UNDERCOATING BLACK BRUSH CAN 1,3 KG

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- \cdot 7.3 *Specific end use*(s) *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Protection of hands:



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

(Contd. on page 5)

Printing date 08.02.2021 Version number 58 Revision: 11.03.2020

Trade name: MOTIP® BITUMEN UNDERCOATING BLACK BRUSH CAN 1,3 KG

(Contd. of page 4)

Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and ch	nemical properties
General Information	
Appearance:	_
Form:	Pasty
Colour:	Black
Odour:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	130 °C (266 °F)
Flash point:	31 °C (87.8 °F)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C (>392 °F)
•	200 °C (392 °F)
Decomposition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
	0.6 %
Upper:	7 Vol %
	7.0 %
Vapour pressure at 20 °C (68 °F):	2 hPa (1.5 mm Hg)
1 1	2 hPa (1.5 mm Hg)
Density at 20 °C (68 °F):	1.3 g/cm³ (10.8 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C (68 °F):	1520000 mPas

(Contd. on page 6)

Printing date 08.02.2021 Version number 58 Revision: 11.03.2020

Trade name: MOTIP® BITUMEN UNDERCOATING BLACK BRUSH CAN 1,3 KG

	(Contd. of page
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	24.7 %
VOC (EC)	
	316.2 g/l
· VOC-EU%	24.70 %
· Solids content:	75.3 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Oral LD50 >15000 mg/kg (rat) (OECD 401) Dermal LD50 >3400 mg/kg (rab) (OECD 402) Inhalative LC50 / 4h 13.1 mg/l (rat) (OECD 403) LC50 / 96 h 10-30 mg/l (fish)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- $\cdot \textit{Additional toxicological information:}$
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

EC50 / 48 h 10-22 mg/l (daphnia magna)

EC50 / 72 h | 4.6-10 mg/l (Pseudokirchneriella subcapitata)

(Contd. on page 7)

Printing date 08.02.2021 Version number 58 Revision: 11.03.2020

Trade name: MOTIP® BITUMEN UNDERCOATING BLACK BRUSH CAN 1,3 KG

(Contd. of page 6)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

SECTION	/ 14: T	ransport in	<i>formation</i>

- · 14.1 UN-Number
- · ADR, IMDG, IATA

UN1139

· 14.2 UN proper shipping name

· ADR · IMDG, IATA 1139 COATING SOLUTION COATING SOLUTION

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 3 (F1) Flammable liquids.

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label

· 14.4 Packing group

· ADR, IMDG not regulated

· IATA III

(Contd. on page 8)

Printing date 08.02.2021 Version number 58 Revision: 11.03.2020

Trade name: MOTIP® BITUMEN UNDERCOATING BLACK BRUSH CAN 1,3 KG

	(Conto	l. of page
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user · EMS Number:	Warning: Flammable liquids. F-E, <u>S-E</u>	
· 14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.	
· Transport/Additional information:		
· ADR · Remarks:	> 450 l: 3 F1, III	
· IMDG · Remarks:	> 30 l: 3, III	
· UN ''Model Regulation'':	UN 1139 COATING SOLUTION, 3	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: R&D legislation and regulatory advisor
- $\cdot \textit{Contact:} \ msds@nl.motipdupli.com$
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)

Printing date 08.02.2021 Version number 58 Revision: 11.03.2020

Trade name: MOTIP® BITUMEN UNDERCOATING BLACK BRUSH CAN 1,3 KG

(Contd. of page 8)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity – Category 3

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.