

SPECTROPRIME is a coloured primer/surface for fast spot priming providing a smooth pin hole free surface easily sanded or used wet on wet. Can be used directly onto difficult substrates as an excellent etch primer.

Suitable substrates (cleaned & abraded)


- Suitably prepared Aluminium, Stainless Steel and Galvanised steel
- Suitable for most types of plastics excluding PE

Physical and chemical data

Basis of binder	Nitro Cellulose Resin
Colour	Various
Coverage	1.0m ²
Temperature resistance	Up to 90°C
Storage stability	10 years in appropriate storage (-10°-25°C, relative air humidity of max. 60%)
Size	400ml
VOC content	338 g/400ml

Application guide


- Remove all rust from metal surfaces
- Clean surface with a suitable degreaser then abrade
- Carry out test spray
- Areas to be sprayed must be free of grease, dust and dry
- For professional use only
- Wear an appropriate respirator



Shake aerosol for at least two minutes, after agitator ball is free



3 Minutes



Apply in cross coats from distance of 250mm from object




Allow 5-10 mins flashoff between coats



1-2 coats @ 10 - 20 m



After use, turn aerosol upside down and empty valve



10 - 15 minutes @ 20°C

Features and benefits

- Coloured spot primer for greater topcoat opacity
- Excellent adhesion and anti-corrosive properties
- Very fast drying
- Excellent smooth surface finish
- Adheres to a wide range of substrates including most plastics

Environmentally sound

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.



CODE:

GREY SHADE 2

GREY SHADE 4

GREY SHADE 6

BLACK

RED

BLUE

GREEN

YELLOW

WHITE

DISCLAIMER OF LIABILITY

The information contained in this Technical Data Sheet is correct to the best of Alpha Coatings Limited trading as Capella Solutions Group's ("Capella") knowledge, however, you must satisfy yourselves that the Goods are suitable for your needs by way of your independent testing or other processes. Capella makes no warranty, representation, or guarantee regarding the information contained in the Technical Data Sheet or the suitability of its products and services for any particular purpose, nor does Capella assume liability arising out of the application or use of the Goods other than any liability which cannot be limited by law including but not limited to liability for: (a) death or personal injury caused by negligence; (b) fraud or fraudulent misrepresentation; and (c) breach of the terms implied by section 12 of the Sales of Goods Act 1979, in such circumstances Capella's total liability shall not exceed the cost of the Goods. Capella's total liability includes liability in contract, tort, negligence, breach of statutory duty, or otherwise. It is the Customer's responsibility to ensure that the guidance on the Technical Data Sheet is followed.