



PANEL BAG SET 2PC

MODEL NO: VS9113

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instruction manual

1. SAFETY

- WARNING!** Ensure Health & Safety, local authority, and general workshop practice regulations are adhered to when using this equipment.
- ✓ Familiarise yourself with the application and limitations of the panel bag set, as well as the potential hazards.
- ✓ Maintain the set in good condition.
- ✓ Replace damaged parts.
Use genuine parts only. Unauthorised parts may be dangerous and will invalidate the warranty.
- ✓ Maintain correct balance and footing. Ensure floor is not slippery and wear non-slip shoes.
- ✓ Keep children and unauthorised persons away from the working area.
- ✗ **DO NOT** put hands/fingers in apertures created by bags without first inserting a mechanical chock to prevent accidental injury
- ✗ **DO NOT** use the panel bags for purposes other than those for which they were designed.
- ✗ **DO NOT** over-inflate.
- ✗ **DO NOT** use on doors fitted with air bags.
- ✗ **DO NOT** use when you are tired, under the influence of alcohol, drugs or intoxicating medication.
- ✓ Deflate bag prior to storage.
- ✓ Store in a clean, dry place.

2. INTRODUCTION

Multi-purpose durable air cushion devices with rigid edges and fine air control valve. Suitable for positioning panels, bonnets and boots, prior to fitment. 2mm thickness and semi-rigid construction allow bags to be slid between window frame and weather-stripping for improved access for emergency vehicle opening tools. Soft air cushion is gentle on paintwork, frame, beadings and glass. Can also be used for positioning kitchen units, windows and doors.

3. SPECIFICATION

Model No:.....**VS9113**
 Load Capacity: 135kg
 Bag Dimensions (W x H):128 x 270mm
 Minimum/Maximum Thickness2mm-80mm



4. ASSEMBLY & INSTALLATION

- 4.1. To adjust body panels
 - 4.1.1. Place a panel air bag between the vehicle body and panel to be fitted (bonnet, boot etc.) at the point that needs adjusting.
 - 4.1.2. Ensure the pump valve is closed (fully clock-wise), pump air into the bag by squeezing the bulb on the pump, (taking care not to over-inflate) moving the panel to the required position.
 - 4.1.3. When the panel has been fitted, simply deflate the panel bags by turning the release valve anti-clockwise.
 - 4.1.4. The rigid construction allows the bag to be inserted between a window frame and weather stripping on a vehicle door etc. To ease this operation, first lubricate the bag with a water-soluble lubricant such as washing up liquid. When using the bag to gain access through a door etc., ensure that a mechanical means of chocking the door is employed before inserting fingers or hands etc.

5. MAINTENANCE

- 5.1. When the bags are not in use ensure they are deflated, clean and stored in a dry location.
 - 5.1.1. Inspect before use to check for any sign of damage. The bags cannot be repaired; any sign of damage must result in the bag being discarded.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



01284 703534



sales@sealey.co.uk



www.sealey.co.uk