

**URKI-CUT**  
 CUTTING COMPOUND

Edition: 020 2011/11  
 Cod: 0200000010.00000.020

### APPLICATION

URKI-CUT is an effective and high quality cutting compound, developed for using on Car Refinishing clear coats. Its formulation eliminates quick and effectively mistakes and surface scratches, over-spraying and P1000 - P1500 sanding marks. It has a high cutting degree that gives very high gloss, without blooming or holograms. The solid and liquid ingredients of its formulation minimize the dust, reducing the pollution of the working area. The remains are easy to clean. The use of URKI-GLOSS in the polishing is recommended. High cutting power with a medium polishing level. It can be used on freshly-repaired or old coatings. Does not contain silicones.

### PHYSICAL PROPERTIES

Density at 20°C (g/cc)	1,5 ± 0,02
Grinding Fineness (µ)	No lumps
Supply viscosity at 20°C	Liquid
V.O.C. (g/l)	< 200 (2004/42/CE) IIB (A) (200)
Type of product	
Colour	White

### APPLICATION INSTRUCTIONS

It is important to apply an adequate pressure on the polishing machine in the first passes on the surface for eliminating the marks and defects.

Cutting tool: dense and hard sponge for cutting processes.



Clean and wet



P-1000  
P-1500



1200-2000 rpm



Clean

### STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended. Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.