

# **TECHNICAL DATA SHEET**

BERNARDO ECENARRO, S.A. Poligono Industrial San Lorenzo s/n 20870 Elgoibar (SPAIN) Tel.: +34 943 74 28 00 Fax: +34 943 74 06 03 www.bernardoecenarro.com

Page 1 from 1

URKI-GLOSS POLISHING COMPOUND

> Edition: 020 2011/11 Cod: 020000020.00000.020

### APPLICATION

URKI-GLOSS is on effective and high quality polishing compound designed for being used on any type of paint. Its formulation will eliminate quickly and effectively the cutting and sanding (P2500 - P3000) marks. A very high gloss level can be achieved, with a mirror effect. The solid and liquid ingredients of its formulation minimize the dust, reducing the pollution of the working area. High gloss with a medium cutting level. It can be used on freshly-repaired or old coatings. Does not contain silicones.

#### **PHYSICAL PROPERTIES**

Density at 20°C (g/cc)	$1,00 \pm 0,02$
Grinding Fineness (µ)	No lumps
Supply viscosity at 20°C	Liquid
V.O.C. (g/l)	130 (2004/42/CE) IIB (A) (200)
Type of product	
Colour	White

## **APPLICATION INSTRUCTIONS**

It is important to apply an adequate pressure on the polishing machine in the first passes on the surface for eliminating the marks and defects.

Polishing tool: soft sponge for polishing processes.

P3000

Do not use the cutting sponge. The remains are easy to clean. Clean with micro-fibre cloths.









Clean with a micro-fibres cloth

#### STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended. Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.