

SPRAY URKI-PLAST
STRUCTURE PAINT FOR PLASTICS

APPLICATION

Flexible Acrylic Paint specially designed for the painting of vehicles bumpers. Satin structured appearance quite similar to the original bumpers.

It is used as an adhesion promoter primer for plastics. May be repainted with Acrylic, Single-Coat and Bi-Topcoats.

A wide variety of textures may be obtained if the application conditions are varied.

VOC Content is <840 g/l (2004/42/CE) IIB (E) (840).

SURFACE PREPARATION

Remove dirt with water and soap; once the surface to be painted is dry, degrease with thinner nº 94. In case of plastics with difficult adhesion, use the Adhesion Promoter previously.

Do not apply on Synthetic Enamels (alkyd based).

APPLICATION INSTRUCTIONS

Shake the can for 2-3 minutes before applying URKI-PLAST Spray.

Application in 1 or 2 coats (leave 5+-10 minutes between them)

After using, turn down the can and press for cleaning the nozzle.



Painting range
20-30 cm



40-60 cm



5-10 min.



Dry 30 min.

FEATURES OF DRY FILM

Colour	9005 Black, 7870 Grey
Gloss 60°-60°	Matt
Second layer	4 h.

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended.

PRECAUTION: In any case the cans must be exposed over 50°C.

Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.