

SAFETY DATA SHEET EGR & Carb Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name EGR & Carb Cleaner

Product number HMTN0201A, 52401110134

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier A Holts Car Care Product

Holt Lloyd International Ltd

Barton Dock Road

Stretford Manchester

M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com

Contact person Regulatory Affairs, Contact Email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358

9167

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or Xn;R48/20. Repr. Cat. 3;R63. Xi;R38. F+;R12. R52/53,R67. **1999/45/EC)**

2.2. Label elements

Pictogram







Signal word

Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H315 Causes skin irritation.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with local regulations.

Contains TOLUENE, ACETONE, Naphtha (petroleum), hydrotreated light

Detergent labelling ≥ 30% aromatic hydrocarbons, 5 - < 15% aliphatic hydrocarbons

Supplementary precautionary

statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

P312 Call a POISON CENTER/ doctor if you feel unwell.
P314 Get medical advice/ attention if you feel unwell.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TOLUENE		30-60%
CAS number: 108-88-3	EC number: 203-625-9	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67	
Skin Irrit. 2 - H315		
Repr. 2 - H361d		
STOT SE 3 - H336		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		

ACETONE		10-30%
CAS number: 67-64-1	EC number: 200-662-2	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Xi;R36 R66 R67	
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

BUTANE	10-309	6
CAS number: 106-97-8	EC number: 203-448-7	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Gas 1 - H220	F+;R12	
Press. Gas		

ISOBUTANE		5-10%
CAS number: 75-28-5	EC number: 200-857-2	
Classification Flam. Gas 1 - H220 Press. Gas	Classification (67/548/EEC or 1999/45/EC) F+;R12	

Naphtha (petroleum), hydrotreated light		5-10%
CAS number: 64742-49-0	EC number: 265-151-9	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
Skin Irrit. 2 - H315		
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.

Ingestion Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at

rest in a position comfortable for breathing. Do not induce vomiting. Never give anything by

mouth to an unconscious person. Do not induce vomiting.

Skin contact Remove affected person from source of contamination. Get medical attention if any discomfort

continues.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during

firefighting

Move containers from fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and

eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air

contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 191 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 574 mg/m3(Sk)

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm Short-term exposure limit (15-minute): OES 800 ppm

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment





Eye/face protection The following protection should be worn: Chemical splash goggles.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. EN374 It is recommended that gloves

are made of the following material: Rubber (natural, latex).

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

Hygiene measuresWash hands at the end of each work shift and before eating, smoking and using the toilet.

Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Do not smoke in work area.

Respiratory protection No specific recommendations. Respiratory protection may be required if excessive airborne

contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Odour aromatic hydrocarbons

Initial boiling point and range 63° - 100°C @

Flash point -26C°C

Relative density 0.686 @ °C

Auto-ignition temperature 200°C

Viscosity 0.44mm² @ 40°C

9.2. Other information

Volatility 95.89%

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition

products

Thermal decomposition or combustion products may include the following substances:

Thermal decomposition or combustion products may include the following substances: Acrid

smoke or fumes. Carbon dioxide (CO2). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Vapours may cause headache, fatigue, dizziness and nausea. Extensive use of the product in

areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following

overexposure may include the following: Headache.

Ingestion May cause chemical burns in mouth, oesophagus and stomach. Harmful: may cause lung

damage if swallowed.

Skin contact Irritating to skin. Prolonged or repeated exposure may cause severe irritation.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Route of entry Inhalation Skin and/or eye contact

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment. May cause long-term adverse effects in the aquatic

environment. The product contains a substance which is toxic to aquatic organisms and which

may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion. Avoid the spillage or runoff entering drains, sewers or

watercourses. Toxic to aquatic organisms.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 58

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group None

IMDG packing group None

ADN packing group None

ICAO packing group None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation Dangerous Substances Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended). Detergents Regulation EC 648/2004

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 24/11/2016

Revision 3

Supersedes date 15/07/2014

SDS number 14592

Risk phrases in full R11 Highly flammable.

R12 Extremely flammable. R36 Irritating to eyes. R38 Irritating to skin.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R63 Possible risk of harm to the unborn child. R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: may burst if heated H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.