

PROMATIC - STONECHIP (1LT)

Page: 1

Compilation date: 28/06/2011

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PROMATIC - STONECHIP (1LT)

Product code: SC-1

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: PROMATIC

Second Avenue

Chatham

Kent

ME4 5AU

England

Tel: 01634 823900

Fax: 01634 813807

Email: sales@alphacoatings.co.uk

1.4. Emergency telephone number

Emergency tel: 01634 823900

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xi: R38; Xn: R48/20; Xn: R63; -: R67

Most important adverse effects: Highly flammable. Irritating to skin. Harmful: danger of serious damage to health by

prolonged exposure through inhalation. Possible risk of harm to the unborn child.

Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Highly flammable.

Harmful.





Risk phrases: R11: Highly flammable.

R38: Irritating to skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through

PROMATIC - STONECHIP (1LT)

Page: 2

inhalation.

R63: Possible risk of harm to the unborn child.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S36/37: Wear suitable protective clothing and gloves.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TOLUENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
203-625-9	108-88-3	F: R11; Xi: R38; Xn: R48/20; Xn: R63; Xn: R65; -: R67	-	10-30%
ACETONE				
200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	-	1-10%
N-BUTYL ACE	TATE			
204-658-1	123-86-4	-: R10; -: R66; -: R67	-	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Substance with a Community workplace exposure limit.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

PROMATIC - STONECHIP (1LT)

Page: 3

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool

containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

PROMATIC - STONECHIP (1LT)

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

TOLUENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA:	15 min. STEL:	8 hour TWA:	15 min. STEL:
UK	191 mg/m3	574 mg/m3	-	-

ACETONE

UK	1210 mg/m3	3620 mg/m3	-	-
----	------------	------------	---	---

N-BUTYL ACETATE

UK	724 mg/m3	966 mg/m3	-	-
----	-----------	-----------	---	---

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Various

Odour: Characteristic odour

Solubility in water: Insoluble

Viscosity: Viscous

Flash point°C: <21 Relative density: 1.330

VOC g/I: 384.64

PROMATIC - STONECHIP (1LT)

Page: 5

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Irritation	DRM	Hazardous: calculated
Repeated dose toxicity	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

PROMATIC - STONECHIP (1LT)

Page: 6

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

PROMATIC - STONECHIP (1LT)

Page: 7

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: R10: Flammable.

R11: Highly flammable.
R36: Irritating to eyes.

R38: Irritating to skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R63: Possible risk of harm to the unborn child.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.