

TAR & ADHESIVE REMOVER

Page: 1

Compilation date: 13/12/2012

Sent to: VINNY BYRNE LTD Revision No: 1

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: TAR & ADHESIVE REMOVER

REACH registered name: METHYL ETHYL KETONE

REACH registered number(s): 01-2116457290-43-XXX

CAS number: 78-93-3

EINECS number: 201-159-0

Index number: 606-002-00-3

Product code: \$163 Synonyms: MEK

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Company name: SOLVENTS WITH SAFETY LTD

UNITS 1-4

PLUMTREE FARM INDUSTRIAL ESTATE

HARWORTH
DONCASTER
DN11 8EW
United Kingdom

**Tel:** 01302711733 **Fax:** 01302 711744

Email: sales@solventswithsafety.co.uk

# 1.4. Emergency telephone number

Emergency tel: 08445605341

### **Section 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Highly flammable liquid and

vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

#### 2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

[cont...]

TAR & ADHESIVE REMOVER

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

#### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

# 3.1. Substances

Chemical identity: ETHYL METHYL KETONE

**CAS number:** 78-93-3 **EINECS number:** 201-159-0

REACH registered number(s): 01-2116457290-43-XXX

# Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

# TAR & ADHESIVE REMOVER

Page: 3

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

# 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water

spray to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

# 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

# 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

TAR & ADHESIVE REMOVER

Page: 4

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

# 8.1. Control parameters

### Workplace exposure limits:

#### Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK    | 600 mg/m3  | 899 mg/m3    | -          | -            |

### Hazardous ingredients:

#### **ETHYL METHYL KETONE**

### Workplace exposure limits:

### Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK    | 600 mg/m3  | 899 mg/m3    | -          | -            |

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

# 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

### Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Alcoholic

Solubility in water: Soluble

Viscosity: Viscous

TAR & ADHESIVE REMOVER

Page: 5

Boiling point/range°C: >35 Flammability limits %: lower: 1.8

upper: 11.5 Flash point°C: -6

Autoflammability°C: 514 Vapour pressure: 101 HpA

#### 9.2. Other information

Other information: No data available.

### Section 10: Stability and reactivity

# 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

# 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

# Relevant hazards for substance:

| Hazard                        | Route | Basis                 |  |
|-------------------------------|-------|-----------------------|--|
| Serious eye damage/irritation | OPT   | Hazardous: calculated |  |
| STOT-single exposure          | -     | Hazardous: calculated |  |

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

TAR & ADHESIVE REMOVER

Page: 6

# Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

#### Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

**Recovery operations:** Solvent reclamation/regeneration.

Waste code number: 08.01.11

**Disposal of packaging:** Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

#### 14.1. UN number

UN number: UN1193

14.2. UN proper shipping name

Shipping name: ETHYL METHYL KETONE (METHYL ETHYL KETONE)

14.3. Transport hazard class(es)

Transport class: 3

# 14.4. Packing group

Packing group: ||

# TAR & ADHESIVE REMOVER

Page: 7

### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: Yes

#### 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 2

# **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

# 15.2. Chemical Safety Assessment

#### **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.