



## **Product Data**

### **Simoniz Gloss Black – SIMP15D**

#### **Product Characteristics:**

High gloss

Excellent hardness / durability

Great coverage / hiding power

Outstanding weather resistance (including resistance to UV)

Suitable for both interior and exterior use

#### **Technical Data:**

Coverage – 1 m<sup>2</sup> (approx.) / 500 mL can<sup>#</sup>

Temperature Resistance – 120 °C

Touch Dry Time – 20 minutes\*

Overcoat Time – 2 hours\*

# Coverage achieved per can is dependent on thickness of applied coat(s).

\* @ 20 °C. Actual drying / overcoat times depend on ambient temperature, humidity and coat thickness.

#### **Surface Preparation:**

Clean area to be treated of dirt, rust, oil or grease etc. prior to use. Mask off any areas not to be painted.

#### **Tips:**

Shake vigorously before use. Apply in thin, even coats. For best result use in conjunction with a suitable Simoniz primer and Simoniz Clear Lacquer (SIMP22D).

#### **Holt Lloyd International Ltd**

Unit 100, Barton Dock Road, Stretford, Manchester, M32 0YQ

Tel: +44 (0)161 866 4800 Fax: +44 (0)161 866 4854

E-mail: [info@holtsauto.com](mailto:info@holtsauto.com) [www.holtsauto.com](http://www.holtsauto.com)