# PINTURAS JUNO

NATUR-SELL CODE: 21100

## **DESCRIPTION**

A primer sealer based on aqueous-dispersed acrylic resins and selected pigments, which provide high resistance and flexibility.

# **USAGE: INDOOR - OUTDOOR**

Wood and masonry surfaces.

# **CHARACTERISTICS**

•	Finish Colour	Matt White
•	Viscosity	Min 25 P S/FR 1007
•	Density	1.35 +/-0.05 S/FR1001
•	Drying time	To the touch: 1-2 hours
		Second coat: Minimum: 12 hours
		Maximum: Indefinite
•	Diluent	Water
•	Solids in volume	42% theoretical
•	Health & Safety	Aqueous-phase paint product: exempt from labelling
•	Guidance coverage	8 - 10 m <sup>2</sup> / Lt / coat
•	VOC content	Max 50 g/l

# SURFACE PREPARATION

#### WOOD

It must be clean and dry, grease-free and sanded. Before applying the finishing coat, sanding down the surface is recommended.

#### **MASONRY**

Surfaces must be dry and efflorescence-free, and in the case of cement and plaster, also neutralised with 10% Hydrochloric Acid or vinegar. Rinse with water and allow to dry.

Previously painted surfaces, when in good condition, can be painted directly once washed and lightly sanded in order to fully remove the gloss. If the paint is in a poor condition, it must be thoroughly removed. Clean up and treat as new.



# **APPLICATION INSTRUCTIONS**

Brush, roller or spray gun.



Use Junoral Colorant with water, at ratios not exceeding 3 %.



Water

# **REPAINTING**

Any synthetic, epoxy or polyurethane based enamel can be used for repainting.

# **OBSERVATIONS**

Stir the recipient contents thoroughly until evenly mixed.

# **PACKAGING**

Metal container. Sizes: 0.750 and 4 litres.

Date: January 2007/Revision: 3

N.B.: Our technical instructions and advice, whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, it must only be construed as an indication WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the procedures and purposes intended. The application, use and processing of the products supplied by us are carried out outsi de and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.

