PINTURAS JUNO DATA SHEET

ODOURLESS COVER-STAIN SEALER With Plioway

CODE: 21350

DESCRIPTION

An anti-grease, anti-stain, antifungal, anti-damp, odourless isolating sealer, with high whiteness, bonding and covering properties. Matt finish, washable and non-yellowing.

USAGE: INDOOR

Recommended for any surface stained by damp, smoke, nicotine, etc.

CHARACTERISTICS

• Finis	sh	Matt
• Cold	our	White
• Visc	cosity	Min 100 Poises S/FR1007
• Den	sity	1.38 +/-0.05 g/cc S/FR1001
	ng time	To the touch :4 hours
		Second coat: Minimum: 24 hours
		Maximum: Unlimited
• Solie	ds in volume:	39,5 %. Theoretical
 VOC 	C content:	Maximum: 450 g/l.
Cov	erage	7.5 m ² / Lt / coat
• Solv	vent	D-69 (odourless)

SURFACE PREPARATION

WOOD

It must be clean and dry, grease-free and sanded.

IRON AND STEEL

Remove grease and rust, and prime with **Metalex Red Lead** or an appropriate antioxidant agent.

ALUMINIUM & GALVANISED SURFACES

Once cleaned, prime with Multipurpose Primer.

MASONRY

Surfaces must be dry and efflorescence-free, and in the case of cement and plaster, also neutralised with 10% Hydrochloric Acid. For binding, hardening and sealing of pulvurent materials surfaces, apply a coat of **Akril 80 Varnish.**



Previously painted surfaces, when in good condition, can be painted directly once washed and lightly sanded in order to fully remove the gloss. If the paint is in a poor condition, it must be thor oughly removed. Clean up and treat as new.

APPLICATION INSTRUCTIONS

Directly, with a brush or roller.

CLEANING

D-16 Solvent or Universal Solvent

REPAINTING

With the same product.

Plastic paint repainting in less than 30 days, may lead to the reappearance of old stains.

OBSERVATIONS

Stir the recipient contents thoroughly until evenly mixed. For best results, apply two product coats without diluting.

PACKAGING

Lithographed metal container. Sizes: 0.750 / 4 and 15 litres.

Date: January 2007/Revision: 4

N.B.: Our technical instructions and advice, whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, it must only be construed as an indication WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the procedures and purposes intended. The application, use and processing of the products supplied by us are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, reg ardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.

