## PINTURAS JUNO DATA SHEET

# **HIDROPRIMER**

**CODE: 81007** 

### **DESCRIPTION**

Anti-dust paint based on water-emulsified acrylic resins. This solvent-free product has outstanding penetration, adherence and resistance properties. Ideal to solve adherence problems in mineral construction materials.

#### **USAGE: INDOOR - OUTDOOR**

As a primer coat before painting, suitable for perlite, concrete, gypsum, cement, fibre cement and brickwork substrates.

As fixing agent for tempera, soot and lime.

As odourless water-based varnish to protect mineral surfaces.

#### **CHARACTERISTICS**

•	Finish	Gloss
•	Colour	Colourless
•	Drying time	Approx. 30 minutes
		Second coat: Minimum 2 hours
		Maximum: Indefinite
•	Diluent	Water
•	Coverage	Variable, depending of substrate porosity Guidance: 4-8 m² / Lt / coat
•	Flash point	Non flammable
•	VOC content	Max 15 g/l

### **APPLICATION INSTRUCTIONS**

- Brush, roller or spray gun.
- Pneumatic equipment.
- Stir the recipient contents thoroughly until evenly mixed.
- Surfaces must be clean, dry and efflorescence -free.
- Do not apply on substrates with temperatures below 5°C, or overly heated .
- When used as a varnish and depending on the substrate porosity, it may be diluted with water to a chieve ratios up to 50%, obtaining the desired texture and effect.
- To improve its penetration power, use 1 part Hidrocril mixed with 4 parts water.



## **OBSERVATIONS**

This mixture can be prepared in volume or in weight.

Once diluted in water, the whole amount must be used.

# **PACKAGING**

Plastic container. Sizes: 0.750 / 4 and 20 litres.

Date: January 2007/Revision: 6

N.B.: Our technical instructions and advice, whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, it must only be construed as an indication WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the procedures and purposes intended. The application, use and processing of the products supplied by us are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our product s according to our General Sale and Supply Conditions.

