

U-POL®

PLASTIKIT

Professional Glass Fibre Kit

Description	<p>U-POL Plastikit is a polyester resin kit, containing resin, MEKPO hardener, glass fibre, mixing cup, and plastic gloves.</p> <p>U-POL Plastikit has been developed for the repair of holes, splits, cracks and tears in most materials including metal, wood, hard plastic, bricks etc.</p> <p>U-POL Plastikit can also be used as a construction material to manufacture storage tanks etc.</p> <p>U-POL Plastikit offers perfect adhesion to most surfaces and is a solid base for most paint systems.</p> <p>U-POL Plastikit can be used</p> <ul style="list-style-type: none">• to repair, construct and create.• Is resilient, permanent, waterproof.• Has 1000's of uses• Is quick and easy to use
Surface preparation and instructions for use	<p>Prepare well. Surface must be clean, dry, and free from all traces of grease, loose matter and rust. Abrade with P40 paper.</p> <p>Cut sufficient matting in order to cover the surface.</p>
Health and Safety Statement	<p>FOR PROFESSIONAL USE ONLY. Read full instructions before use.</p> <p>IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.</p>
Hardener	<p>To activate U-POL Plastikit, use 1% to 2% of CAT/2 or CAT/5 hardener. Mix well immediately. Do not use in temperatures below 5°C. Gel time varies depending on the ambient temperature.</p>
Thinner	<p>Dilution of this product is not recommended.</p> <p>Clean tools immediately after use in cellulose thinnorsor acetone.</p>
Application	<p>Paint the prepared area with activated resin using an old brush.</p> <p>Apply a workable size of mat to the area and then using a stiff brush, stipple the glass fibre until it is "wetted".</p> <p>Clean tools immediately.</p> <p>Leave the resin to dry and repeat the application with more strips of mat until the desired effect is achieved.</p>
Pot Life	<p>The activated resin mixture remains useable and liquid for up to 20 to 30 minutes at 20°C.</p>
Over painting	<p>Sand, clean and dry completely. In order to fill any pin holes or imperfections on the surface, use a U-POL polyester body filler.</p> <p>U-POL Plastikit can be re-covered by the majority of primers and paint systems.</p>
Product Codes	<p>PK1 - Kit contains RE/1, CAT/2 glass fibre matting, 4 mixing sticks, 4 pairs of gloves, 4 measuring jugs.</p> <p>RE/1 - Can of resin 1L.</p> <p>RE/2.5 - Can of resin 2.5L.</p>

U-POL®

	CAT/2 - Bottle of 20ml hardener. CAT/5 - Bottle of 50ml hardener. FIBRE/1 - Matt 0.5m ² FIBRE/5 - Matt 5.0m ²
--	--

U-POL LTD, 4TH FLOOR, THE GRANGE, 100 HIGH STREET, LONDON N14 6BN, UK
Home Sales T: +44(0)20 8492 5920; F:+44(0)20 8181 6911; E: uk.sales@u-pol.com;
Export Sales T: +44(0)20 8492 5900; F:+44(0)20 8150 5605; E: sales@u-pol.com;
Technical T: +44(0)1933 230 310; F:+44(0)1933 425 797; E: technicaldepartment@u-pol.com;
WWW.U-POL.COM