



# SAFETY DATA SHEET

Intulac™ Ultra Satin Topcoat

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Intulac™ Ultra Satin Topcoat  
**Product description** : Fire protection systems.  
**Product type** : Liquid.  
**UFI** : DTS5-P3A9-WVFG-H6HE

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Consumer use Industrial use Professional use	
Uses advised against	Reason
None identified.	-

### 1.3 Details of the supplier of the safety data sheet

Bollom Fire Protection  
 Portobello Industrial Estate  
 Birtley  
 County Durham  
 United Kingdom  
 DH3 2RE  
 Telephone no.: +44 (0) 191 4106611  
 Fax no.: +44 (0) 191 4920125  
 enquiries@tor-coatings.com  
**e-mail address of person responsible for this SDS** : rpmeurohas@rustoleum.eu

### 1.4 Emergency telephone number

National advisory body/Poison Centre

Supplier

**Telephone number** : +44 870 8200418 / +44 2038073798  
**Hours of operation** : 24 / 7

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225

Eye Irrit. 2, H319

STOT SE 3, H335

STOT SE 3, H336

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : Highly flammable liquid and vapour.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Toxic to aquatic life with long lasting effects.

#### Precautionary statements

**General** : P103 - Read carefully and follow all instructions.  
P102 - Keep out of reach of children.  
P101 - If medical advice is needed, have product container or label at hand.

**Prevention** : P280 - Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.

**Response** : P391 - Collect spillage.  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

**Storage** : P403 + P235 - Store in a well-ventilated place. Keep cool.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** : hydrocarbons, aromatic, C9

**Supplemental label elements** : Repeated exposure may cause skin dryness or cracking.

**Supplemental label elements** : Not applicable.

**Supplemental label elements : Detergents - Regulation (EC) No 907/2006**

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable

Special packaging requirements

Intulac™ Ultra Satin Topcoat

## SECTION 2: Hazards identification

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Yes, applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

**United Kingdom: Great Britain**

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
hydrocarbons, aromatic, C9	REACH #: 01-2119455851-35 EC: 918-668-5	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
1,3-dioxolane	REACH #: 01-2119490744-29 EC: 211-463-5 CAS: 646-06-0 Index: 605-017-00-2	≤3	Flam. Liq. 2, H225 Eye Dam. 1, H318	[1]
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	≤0,3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412  <b>See Section 16 for the full text of the H statements declared above.</b>	[1] [2]

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

<b>SCL (Specific Concentration Limits)</b> Not applicable.	Not applicable.
---------------------------------------------------------------	-----------------

Intulac™ Ultra Satin Topcoat

## SECTION 3: Composition/information on ingredients

<p><b>ATE (acute toxicity estimates)</b> Not applicable.</p>	<p>Not applicable.</p>
<p><b>Nanoform</b> <b>Particle characteristics</b> This product does not contains nanomaterials.</p>	<p><b>Particle Size</b> Not applicable.</p>

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness

## SECTION 4: First aid measures

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
halogenated compounds  
carbonyl halides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
- Additional information** : No unusual hazard if involved in a fire.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## SECTION 7: Handling and storage

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Seveso Directive - Reporting thresholds

#### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c E2	5000 tonne 200 tonne	50000 tonne 500 tonne

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

#### United Kingdom: Great Britain

Product/ingredient name	Exposure limit values
toluene	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b> STEL: 384 mg/m <sup>3</sup> 15 minutes. STEL: 100 ppm 15 minutes. TWA: 191 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

No DNELs/DMELs available.

#### PNECs

No PNECs available

## SECTION 8: Exposure controls/personal protection

### 8.2 Exposure controls

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber (0.5mm)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A) (EN 140)



## SECTION 8: Exposure controls/personal protection

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

<b>Physical state</b>	: Liquid.
<b>Colour</b>	: Clear.
<b>Odour</b>	: Aromatic.
<b>Odour threshold</b>	: Not available.
<b>Melting point/freezing point</b>	: Not available.
<b>Initial boiling point and boiling range</b>	: Not available.
<b>Flammability (solid, gas)</b>	: Not available.
<b>Upper/lower flammability or explosive limits</b>	: Not available.
<b>Flash point</b>	: Closed cup: 2°C (35,6°F) [Setaflash / Tag (ASTM D56)]
<b>Auto-ignition temperature</b>	: Not available.
<b>Decomposition temperature</b>	: Not available.
<b>pH</b>	: Not applicable.
<b>pH : Justification</b>	: Product is non-soluble (in water).
<b>Viscosity</b>	: Dynamic (room temperature): 500 to 600 mPa·s [ICI Rotothinner] Kinematic (40°C): >20,5 mm <sup>2</sup> /s
<b>Solubility(ies)</b>	: Insoluble in the following materials: cold water and hot water.
<b>Solubility in water</b>	: Not available.
<b>Miscible with water</b>	: No.
<b>Partition coefficient: n-octanol/ water</b>	: Not applicable.
<b>Vapour pressure</b>	: Not available.
<b>Evaporation rate</b>	: Not available.
<b>Relative density</b>	: 1 to 1,05 [calculated.]
<b>Density</b>	: 1,037272 g/cm <sup>3</sup> [20°C (68°F)] [calculated.]
<b>Vapour density</b>	: >1 [Air = 1]
<b>Explosive properties</b>	: No unusual hazard if involved in a fire.
<b>Oxidising properties</b>	: Not available.
<b>Particle characteristics</b>	
<b>Median particle size</b>	: Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

## SECTION 10: Stability and reactivity

**10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas.

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidising materials

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
hydrocarbons, aromatic, C9 1,3-dioxolane	LD50 Oral	Rat	8400 mg/kg	-
	LC50 Inhalation Vapour	Mouse	10500 mg/m <sup>3</sup>	2 hours
	LC50 Inhalation Vapour	Rat	20650 mg/m <sup>3</sup>	4 hours
	LCLo Inhalation Vapour	Rabbit	32000 ppm	4 hours
	LD50 Dermal	Rabbit	15000 mg/kg	-
	LD50 Dermal	Rat	15 g/kg	-
toluene	LD50 Oral	Rat	3 g/kg	-
	LC50 Inhalation Vapour	Rat	49 g/m <sup>3</sup>	4 hours

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
hydrocarbons, aromatic, C9	8400	N/A	N/A	N/A	N/A
1,3-dioxolane	3000	15000	N/A	20,65	N/A
toluene	N/A	N/A	N/A	49	N/A

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
hydrocarbons, aromatic, C9	Eyes - Mild irritant	Rabbit	-	24 hours 100 UI	-
1,3-dioxolane	Skin - Mild irritant	Rabbit	-	530 milligrams	-
toluene	Eyes - Mild irritant	Rabbit	-	0,5 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Pig	-	24 hours 250 microliters	-
	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-

**Conclusion/Summary**

## SECTION 11: Toxicological information

- Skin** : Based on available data, the classification criteria are not met.  
**Eyes** : Causes serious eye irritation.  
**Respiratory** : May cause respiratory irritation.  
 May cause drowsiness or dizziness.

### Sensitisation

#### **Conclusion/Summary**

- Skin** : Based on available data, the classification criteria are not met.  
**Respiratory** : Based on available data, the classification criteria are not met.

### Mutagenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
hydrocarbons, aromatic, C9	-	-	Negative	Mammal - species unspecified	Route of exposure unreported	-

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
hydrocarbons, aromatic, C9	Category 3	-	Respiratory tract irritation
toluene	Category 3 Category 3	-	Narcotic effects Narcotic effects

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
toluene	Category 2	-	-

### Aspiration hazard

Product/ingredient name	Result
hydrocarbons, aromatic, C9 toluene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

- Information on likely routes of exposure** : Routes of entry anticipated: Dermal, Inhalation.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.  
**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.  
**Skin contact** : Defatting to the skin. May cause skin dryness and irritation.  
**Ingestion** : Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

## SECTION 11: Toxicological information

<b>Eye contact</b>	: Adverse symptoms may include the following: pain or irritation watering redness
<b>Inhalation</b>	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
<b>Skin contact</b>	: Adverse symptoms may include the following: irritation dryness cracking
<b>Ingestion</b>	: No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

<b>Conclusion/Summary</b>	: Based on available data, the classification criteria are not met.
<b>General</b>	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
<b>Carcinogenicity</b>	: No known significant effects or critical hazards.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Reproductive toxicity</b>	: No known significant effects or critical hazards.
<b>Endocrine disrupting properties</b>	: Not available.
<b>Other information</b>	: Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1,3-dioxolane	Acute EC50 6950000 µg/l Fresh water	Daphnia spec. - Daphnia magna	48 hours
	Acute LC50 10000000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours
toluene	Acute EC50 433 ppm Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 12,5 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 6 mg/l Fresh water	Daphnia spec. - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 15,5 ppm Marine water	Crustaceans - Palaemonetes	48 hours

## SECTION 12: Ecological information

	Acute LC50 5,5 mg/l Fresh water	pugio - Adult Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 500 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia spec. - Daphnia magna	21 days

**Conclusion/Summary** : Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
toluene	OECD 301C	100 % - Readily - 14 days	-	-

**Conclusion/Summary** : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
hydrocarbons, aromatic, C9	-	-	Readily
toluene	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
hydrocarbons, aromatic, C9	3.7 to 4.5	10 to 2500	high
1,3-dioxolane	-0,37	-	low
toluene	2,73	90	low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Volatile.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Endocrine disrupting properties** : No known significant effects or critical hazards.

**12.7 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.





**European waste catalogue (EWC)**

## SECTION 13: Disposal considerations

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number or ID number</b>	UN1263	UN1263	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	Paint	Paint	Paint. Marine pollutant (hydrocarbons, aromatic, C9)	Paint
<b>14.3 Transport hazard class(es)</b>	3 	3 	3 	3 
<b>14.4 Packing group</b>	II	II	II	II
<b>14.5 Environmental hazards</b>	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
<b>Additional information</b>	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Limited quantity</b> ≤ 5L <b>Special provisions</b> 640 (C) <b>Tunnel code</b> (D/E)	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Special provisions</b> 640 (C)	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Emergency schedules</b> F-E ; S-E <b>Remarks</b> : ≤ 5L: Limited Quantity - IMDG 3.4	The environmentally hazardous substance mark may appear if required by other transportation regulations. <b>Quantity limitation</b> Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable

#### Other EU regulations

**VOC** :

**VOC for Ready-for-Use Mixture** : IIA/i. One-pack performance coatings. EU limit value for this product : 500g/l (2010.)  
This product contains a maximum of 500 g/l VOC.

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

#### Ozone depleting substances (1005/2009/EC)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EC)

Not listed.

#### Persistent Organic Pollutants (850/2004/EC)

Not listed.

#### Seveso Directive

This product is controlled under the Seveso Directive.

##### Danger criteria

Category
P5c E2

#### United Kingdom: Great Britain

##### References

: EH40/2005 Workplace exposure limits  
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878  
REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

#### International regulations

##### Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

##### Rotterdam Convention on Prior Informed Consent (PIC)

Intulac™ Ultra Satin Topcoat

## SECTION 15: Regulatory information

Not listed.

### [UNECE Aarhus Protocol on POPs and Heavy Metals](#)

List name	Ingredient name	Status
Not listed.		

CN code : 3208 90 91 00

### [Inventory list](#)

<a href="#">Australia</a>	: Not determined.
<a href="#">Canada</a>	: All components are listed or exempted.
<a href="#">China</a>	: All components are listed or exempted.
<a href="#">Europe</a>	: All components are listed or exempted.
<a href="#">Japan</a>	: <b>Japan inventory (CSCL)</b> : Not determined. <b>Japan inventory (ISHL)</b> : Not determined.
<a href="#">New Zealand</a>	: All components are listed or exempted.
<a href="#">Philippines</a>	: All components are listed or exempted.
<a href="#">Republic of Korea</a>	: Not determined.
<a href="#">Taiwan</a>	: All components are listed or exempted.
<a href="#">Thailand</a>	: Not determined.
<a href="#">Turkey</a>	: Not determined.
<a href="#">United States</a>	: Not determined.
<a href="#">Viet Nam</a>	: Not determined.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

### [Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
Flam. Liq. 2, H225	Expert judgment
Eye Irrit. 2, H319	Expert judgment
STOT SE 3, H335	Expert judgment
STOT SE 3, H336	Expert judgment
Aquatic Chronic 2, H411	Expert judgment

### [Full text of abbreviated H statements](#)

#### [United Kingdom: Great Britain](#)



## SECTION 16: Other information

<b>Full text of abbreviated H statements</b>	:	H225	Highly flammable liquid and vapour.
		H226	Flammable liquid and vapour.
		H304	May be fatal if swallowed and enters airways.
		H315	Causes skin irritation.
		H318	Causes serious eye damage.
		H319	Causes serious eye irritation.
		H335	May cause respiratory irritation.
		H336	May cause drowsiness or dizziness.
		H361d	Suspected of damaging the unborn child.
		H373	May cause damage to organs through prolonged or repeated exposure.
		H411	Toxic to aquatic life with long lasting effects.
		H412	Harmful to aquatic life with long lasting effects.
		EUH066	Repeated exposure may cause skin dryness or cracking.

<b>Full text of classifications [CLP/GHS]</b>	:	Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
		Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
		Asp. Tox. 1	ASPIRATION HAZARD - Category 1
		Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
		Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
		Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
		Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
		Repr. 2	REPRODUCTIVE TOXICITY - Category 2
		Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
		STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
		STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of printing** : 31/05/2021

**Date of issue/ Date of revision** : 4/05/2021

**Date of previous issue** : 4/05/2021

**Version** : 4

### Notice to reader

**IMPORTANT NOTE:** The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

**MANUFACTURER'S DISCLAIMER:** the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.