

# zeroflame®

## FIRE RETARDANT TREATMENT

### TECHNICAL DATA

#### PRODUCT DESCRIPTION

Clear fire protection impregnating liquid tested to: BS EN 13501-1:2018

#### APPLICATION

- Solid wood minimum thickness >12mm
- For interior and exterior use

#### FEATURES

- Classifies solid wood as having little or no contribution to fire
- Leaves no visible finish for a natural appearance
- Minimum thickness 12mm
- For interior and exterior use tested to EN 927-6 & EN16755 accelerated weathering: rated as EXT1.
- Clear transparent impregnation
- Non-corrosive
- Non-hazardous
- Odour free

#### DIRECTIONS FOR USE

**Substrate:** Check the surface is absorbent and has not been previously sealed by other coatings. The substrate must be absorbent. It is possible to apply to previously painted or varnished wood if removed completely by sanding back to the original surface.

**Application:** Use as supplied. Do not dilute  
Test on a small area first to ensure finish is acceptable  
Apply 250ml per square metre (4m<sup>2</sup> per litre) to all surfaces by using immersion, spray, brush or roller  
Ambient temperature is above 10°C  
Moisture content of wood should be below 15%  
This product is classed as non-hazardous. The use of eyewear, gloves and mask is good practice and recommended  
Clean tools and overspill with absorbent paper and water

**Drying Times:** 6-12 hours dependent on temperature.

- Overcoating:** Where a final decorative finish is required, substrate must be fully dry before over-coating. We advise checking the moisture content of the substrate prior to application and applying top coat to manufacturer's instructions. A small area of the substrate should be tested for compatibility before the full final coat is applied.
- Storage:** Store above 5°C  
Protect from frost  
Use within 6 months of purchase
- Protection Period:** Fire retardant properties will remain active for the lifetime of the substrate.
- Disposal:** Zeroflame Fire Retardant Treatment is an ecologically friendly material that can be safely disposed of as a household product.

## PRODUCT SPECIFICATION

- Pack sizes:** 5 litre  
20 litre

## LIMITATIONS

- Final Finish:** Natural. Can be overcoated with certain stains, varnishes and paints. (Contact Zeroflame for details of coatings which are suitable).

Discolouration may occur on some types of timber or on heavily knotted wood. If this is a concern it is recommended that a sample area is completed before application to the whole project. Alternatively, application of a compatible varnish or stain may help to overcome this phenomenon if it is unacceptable.

Zeroflame Fire Retardant Treatment may not be suitable for wood-derived particle board or similar as it cannot penetrate. A sample test is recommended to check absorption. Zeroflame Fire Retardant Paint may be more suitable.

Care must be taken to comply with the coverage rate, including allowance for wastage, as inadequate application will affect the fire protection.

## CERTIFICATION

Fire behaviour is classified to BS EN 13501-1:2018 B ,s2, d0.

This information is offered in good faith but without guarantee or liability. In cases of doubt, users should consult with relevant authority. Information given herein is supplied for your guidance only and is based upon the results of controlled tests and experience obtained in the application of the product referred to by Decor Ireland Ltd. As the supplier only, Decor Ireland Ltd has no control over the method or conditions of application of the product and consequently no warranties expressed or implied are intended to be given as to the coverage or performance of the products mentioned or referred to herein and no liability will be excepted for any loss, damage or physical injury from the use or application of the information, data or products mentioned or referred to herein.

Zeroflame is a Trade Mark of Decor Ireland Ltd.

Telephone: Head Office: +44 (0)28 9262 0300 UK Office: 0845 3838333  
Email: [sales@zeroflame.co](mailto:sales@zeroflame.co)