

BARPLAST PREMIUM A M



Product Description

Paint plastic, indoors and outdoors based on acrylic resins in aqueous dispersion and highly colour fast pigments

Confers an effective protection finish and longer life of the film.

Paint with anti-mold preservative.

Carta de Colores

[Carta de colores fachadas 60 colores](#), RAL K-7, NCS Selección 980, NCS Index 1950, NOVA 720, NOVA 2024, EUROTREND



Technical Characteristics

Colour	White and colours
Appearance	Matt
Touch-dry	30 minutes, depending on the thickness applied and atmospheric conditions
Repainting	After 2-4 hours
Yield	8-11 m ² /l, per coat, depending on the state and type of surface
Thinner	Water
Storage	Excellent for up to 1 year/s, unopened, in original packaging, at normal temperature and humidity. Store in places protected against frost.

Properties

- Easy to apply
- Good covering power.
- Filling power
- Finish with maximum whiteness, with high fungicide action, lasting effect and decorative
- Maximum yield
- Shades can be achieved with water based dyes

Applications

Suitable for decoration de of indoors, exceptionally outdoors (mild climates), walls, plaster ceilings, coving, wine cellars and laundries..., for general decoration, with long-lasting, effective protection in the film from stains and mould., for indoors with high temperature and humidity.

Method of Use

- Stir the contents of the pot well
- Apply in even coats
- Application at: Round brush, roller and airless spray gun

Preparation of surfaces

The surface should be clean, dry and free from grease, nitre, flaking and must be consistent.

On mouldy surfaces, clean and disinfect the affected areas.

On surfaces dry and hard (well set plaster) application of 2 coats: the first diluted at 10% and the second slightly diluted or as supplied.

On soft (badly set plaster) or with old plastic paint, temper, lime or other paints surfaces: Remove soft, crumbling, flaking parts... and totally remove limescale

Seal adequately with SELLAFOND AL AGUA and proceed as in the previous case.

Recommendations before application

Do not apply in temperatures below 5°C.

Other data

Packaging 4L, 15L

Remarks

Shake contents of containers before use.
For toxicological standards, consult FICHA DE SEGURIDAD.
Do not store opened or started containers.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 26-11-2013 This sheet replaces all previous versions.