

## BARPLAST BASIC

### Product Description

Paint plastic, matt, covering, decorative, for indoor walls and ceilings based on special acrylic resin in aqueous solutions and highly colour fast pigments



### Technical Characteristics

Colour	White
Appearance	Matt
Touch-dry	30-60 minutes, depending on the thickness applied and atmospheric conditions
Repainting	After 2-4 hours
Yield	5-9 m <sup>2</sup> /l, per coat, depending on the state and type of surface
Thinner	Water
Storage	Excellent for up to 1 year/s, unopened, in original packaging, at normal temperature and humidity. Store in places protected against frost.

### Properties

- Easy to apply
- Good covering power.
- Maximum yield
- Finish plain, decorative and even
- Excellent whiteness
- Shades can be achieved with water based dyes

### Applications

Suitable for: decoration with indoors, walls and plaster ceilings, coving. For general decoration

### Method of Use

- Stir the contents of the pot well
- Apply in even coats
- Application at: Round brush, roller and airless spray gun

### Preparation of surfaces

The surface must be clean and dry and free from grease, nitre, old paint and must be consistent, free from loose, crumbling or flaking particles.  
On surfaces dry and hard (well set plaster) application of 2 coats: the first diluted at 10% and the second slightly diluted or as supplied.  
On soft (badly set plaster) or with old plastic paint, temper, lime or other paints surfaces: Remove soft, crumbling, flaking parts... and totally remove limescale  
Seal adequately with SELLAFOND AL AGUA and proceed as in the previous case.

### Recommendations before application

Do not apply in temperatures below 5°C.

### Other data

Packaging 15L

### Remarks

Shake contents of containers before use.  
For toxicological standards, consult FICHA DE SEGURIDAD.

Do not store opened or started containers.  
Apply with good air renewal.

*This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 16-02-2012 This sheet replaces all previous versions.*