



TECHNICAL SHEET



SO/4020

WATERBORNE DEGREASER



DESCRIPTION

Water-based degreaser for the removal of grease, oil and other pollutants from metals in the surface preparation process before painting.

APPLICATION

Soak a cloth with SO/4020 and rub on the surface to be cleaned and then dry it with a dry cloth. It can also be used before and after sanding in multi-layer systems.



SAFETY AND HYGIENE

Recommendable to use the appropriate personal protective equipment during application to avoid irritation of breathing tract, skin and eye irritation.

STORAGE

Keep covered in a dry and ventilated place, avoiding direct exposure to sunlight. We advise temperature above 5°C, recommended between 15-30°C.



SO/4020

WATERBORNE DEGREASER

VOC

SO/4020 has a lower organic solvent content than the traditional, compliant with the European Norm 2004/42/CE IIB [A]<200g/l

The information contained in this Technical Data Sheet is based on our knowledge and experience and with it we try to advise and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. FOR PROFESSIONAL USE EXCLUSIVELY.

SINNEK

Ugarte Industrialdea, 147
20720 Azkoitia (Gipuzkoa) - Spain

T: + 34 943 74 28 00
sinnek@sinnek.com
www.sinnek.com