

Douglas

DECORATIVE RANGE

OXIDE PAINT

LONG LASTING ANTI-CORROSIVE GLOSS PAINT
WITH A HIGH QUALITY ALKYD RESIN FINISH



**CURUST
INDUSTRIES
LTD.**

Units 12 & 13,
Southern Cross
Business Park,
Bray, Co. Wicklow,
Ireland.

email: info@curust.ie

www.curust.ie

e 5Ltr



PREPARATION

Ensure the surface is clean, dry and free from any wax, oil, grease and dirt. Remove any loose and flakey material before applying product. On new unpainted surfaces it may be necessary to prime first with a suitable primer. If going straight onto galvanised metal be sure to prepare the surface with a mordant solution or suitable primer in advance of applying paint.



APPLICATION

Douglas Oxide Paint can be used as a single-coat general purpose protective coating on any type of normally prepared surface. It is a high performance coating made from synthetic resins, formulated for ease of use by spray, brush or roller. Paint should be stirred thoroughly before use taking care to mix the paint at the bottom of the tin. Supplied ready for use but, if necessary, thin with Douglas White Spirits.



COVERING CAPACITY

Approximately 10 square metres per litre.

DRYING TIME

Surface dry 3-6 hours. Allow to dry overnight if applying more than one coat.

CLEAN UP

Remove as much product from equipment as possible before washing with Douglas White Spirits. Do not empty into drains or waterways. Some local authorities may have special facilities for disposal of waste coatings.

EU limit for this product (Cat: A/i) is 500g/l. This product contains a maximum of 500g/l VOC.

• INDUSTRIAL AND
AGRICULTURAL USE

• EXCELLENT COVERING
POWER ON ALL TYPES OF
SUBSTRATES

• INTERIOR AND EXTERIOR
USE

• SUITABLE FOR USE OVER
BLOCKWORK, STEEL
SHEETS, ASBESTOS
SHEETING OR WOOD

• PROTECTS AGAINST
WEATHERING AND
CORROSION

• LEAD AND CHROME FREE

DANGER

Flammable liquid and vapour. Suspected of damaging fertility or the unborn child. Toxic to aquatic life with long lasting effects. Causes damage to organs through prolonged or repeated exposure.

Keep out of reach of children. Read label before use. If medical advice is needed, have product container or label at hand. Keep away from heat, sparks, open flames, other ignition sources and hot surfaces. - No smoking. Avoid breathing gas, vapour or spray. In case of inadequate ventilation wear respiratory protection. Avoid release to the environment. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Do not use solvents or thinners. Call a doctor if you feel unwell. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations. In case of fire use water spray, dry powder, foam or carbon dioxide to extinguish. Hazardous ingredients: white spirit. Contains 2-butanone oxime; 2-butanone oxime; solvent naphtha (petroleum), medium aliphatic; cobalt (11) 2-ethylhexanoate. May cause an allergic skin reaction.

