

SCAN TO WATCH

How to apply H2O Liquid Prime & Mask



SAVE TIME & MONEY WITH 2-IN-1 PRIME & MASK

- Paint & Peel
- Extremely fast
- Clean removal
- Dual purpose primer & peelable mask
- Can be sprayed, rolled or brush applied
- Perfect for glassed timber doors



AVAILABLE IN STORE OR ONLINE





STEP 1 - PREPARE SURFACE

Prepare Surface - remove all debris & dust and sand down timber. If the timber had been previously painted ensure the timber is fully sanded before applying h2o.



STEP 2 - APPLY H2O PRIME & MASK

Apply H2O Prime & Mask - stir thoroughly then apply H2O with either a synthetic bristle brush, long nap roller (mid pile) or conventional airless sprayer, recommended typical fluid tip size of 0.013 to 0.017. Theoretical coverage 2m squared /Litre at 200µm DFT



STEP 3 - LET FULLY CURE

Leave to Fully Cure - once H2O prime & mask turns clear (fully cured) - repeat process for a second coat This should take 30-60 minutes



STEP 4 - CUT AROUND & PEEL OFF !

Cut & Peel - carefully cut around inside edge of frames with a sharp knife & simply peel mask away from glass. After use, clean applicators with water



Not to be used on any plastic or PVC surfaces. Always test on intended surface/substrate before use.

AVAILABLE IN -
1 LITRE [H2O-PRIME-1LTR]
5 LITRE [H2O-PRIME-5LTR]



Time Saving
10/10



Peelable up to
3 months exterior
10/10



Easy Release
10/10