



## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860



#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860

**Other means of identification:**

**UFI:** 9PE0-D013-5004-0F7W

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Decorative paint

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

INDUSTRIAS JUNO, S.A.  
Barrio Sakoni, 10  
48950 ERANDIO - Vizcaya - España  
Phone: +34 944 670 062 - Fax: +34 944 675 832  
laboratorio@juno.es  
www.juno.es

**1.4 Emergency telephone number:**

#### SECTION 2: HAZARDS IDENTIFICATION \*\*

**2.1 Classification of the substance or mixture:**

**CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

**Warning**



**Hazard statements:**

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

**Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

**Supplementary information:**

EUH208: Contains Reaction products of Fatty acids, tall-oil, compds. with oleylamine and Fatty acids, C18-unsatd., trimers, compds. with oleylamine. May produce an allergic reaction.

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Substances that contribute to the classification**

Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, <2% aromatics; Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (CAS: 64742-95-6); Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (CAS: 64742-95-6); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (CAS: 64742-48-9)

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)**

**Acute Toxicity Estimate (ATE mix):**

58,2 % (dermal) of the mixture consists of ingredient(s) of unknown toxicity

**UFI:** 9PE0-D013-5004-0F7W

**2.3 Other hazards:**

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

\*\* Changes with regards to the previous version

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\***

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** Mixture composed of pigments and resins

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: Non-applicable EC: 927-241-2 Index: Non-applicable REACH: 01-2119471843-32-XXXX	<b>Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, &lt;2% aromatics<sup>(1)</sup></b>	Self-classified	<b>10 - &lt;25 %</b>
	Regulation 1272/2008	Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	
CAS: 64742-95-6 EC: 265-199-0 Index: 649-356-00-4 REACH: 01-2119486773-24-XXXX	<b>Solvent naphtha (petroleum), light arom., &lt; 0.1 % EC 200-753-7<sup>(1)</sup></b>	ATP ATP01	<b>10 - &lt;25 %</b>
	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336; EUH066 - Danger	
CAS: 64742-95-6 EC: 265-199-0 Index: 649-356-00-4 REACH: 01-2119486773-24-XXXX	<b>Solvent naphtha (petroleum), light arom., &lt; 0.1 % EC 200-753-7<sup>(1)</sup></b>	Self-classified	<b>1 - &lt;10 %</b>
	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	
CAS: 64742-48-9 EC: 265-150-3 Index: 649-327-00-6 REACH: 01-2119486659-16-XXXX	<b>Naphtha (petroleum), hydrotreated heavy, &lt; 0.1 % EC 200-753-7<sup>(1)</sup></b>	ATP ATP01	<b>1 - &lt;10 %</b>
	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(2)</sup></b>	Self-classified	<b>0,1 - &lt;1 %</b>
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(2)</sup></b>	ATP CLP00	<b>0,1 - &lt;1 %</b>
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	
CAS: 22464-99-9 EC: 245-018-1 Index: Non-applicable REACH: 01-2119979088-21-XXXX	<b>2-ethylhexanoic acid, zirconium salt<sup>(1)</sup></b>	Self-classified	<b>0,1 - &lt;1 %</b>
	Regulation 1272/2008	Repr. 2: H361d - Warning	
CAS: Non-applicable EC: 942-330-6 Index: Non-applicable REACH: 01-2120101675-63-XXXX	<b>Reaction products of Fatty acids, tall-oil, compds. with oleylamine and Fatty acids, C18-unsatd., trimers, compds. with oleylamine<sup>(1)</sup></b>	Self-classified	<b>&lt;0,1 %</b>
	Regulation 1272/2008	Acute Tox. 4: H302; Skin Irrit. 2: H315; Skin Sens. 1A: H317; STOT RE 2: H373 - Warning	


<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

<sup>(2)</sup> Substance with a Union workplace exposure limit

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -


**ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860**
**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\* (continued)**

Identification	Chemical name/Classification		Concentration
CAS: 112-34-5 EC: 203-961-6 Index: 603-096-00-8 REACH: 01-2119475104-44-XXXX	<b>2-(2-butoxyethoxy)ethanol<sup>(2)</sup></b>		ATP CLP00
	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	 <b>&lt;0,1 %</b>

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

<sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

\*\* Changes with regards to the previous version

**SECTION 4: FIRST AID MEASURES**
**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES**
**5.1 Extinguishing media:**
**Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

- CONTINUED ON NEXT PAGE -



## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860



#### SECTION 5: FIREFIGHTING MEASURES (continued)

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

##### 6.1 Personal precautions, protective equipment and emergency procedures:

###### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

###### For emergency responders:

See section 8.

##### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

##### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

##### 6.4 Reference to other sections:

See sections 8 and 13.

#### SECTION 7: HANDLING AND STORAGE

##### 7.1 Precautions for safe handling:

###### A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

###### B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

###### C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

###### D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

##### 7.2 Conditions for safe storage, including any incompatibilities:

###### A.- Technical measures for storage

Minimum Temp.:	5 °C
Maximum Temp.:	30 °C
Maximum time:	24 Months

- CONTINUED ON NEXT PAGE -



**ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860**

**SECTION 7: HANDLING AND STORAGE (continued)**

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)		
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	IOELV (8h)	10 ppm	67,5 mg/m <sup>3</sup>
	IOELV (STEL)	15 ppm	101,2 mg/m <sup>3</sup>

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 927-241-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	77 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	871 mg/m <sup>3</sup>	Non-applicable
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1286,4 mg/m <sup>3</sup>	1066,67 mg/m <sup>3</sup>	Non-applicable	837,5 mg/m <sup>3</sup>
Solvent naphtha (petroleum), light arom. , < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1286,4 mg/m <sup>3</sup>	1066,67 mg/m <sup>3</sup>	Non-applicable	837,5 mg/m <sup>3</sup>
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1286,4 mg/m <sup>3</sup>	1066,67 mg/m <sup>3</sup>	Non-applicable	837,5 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	6,49 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	32,97 mg/m <sup>3</sup>	Non-applicable
Reaction products of Fatty acids, tall-oil, compds. with oleylamine and Fatty acids, C18-unsatd., trimers, compds. with oleylamine CAS: Non-applicable EC: 942-330-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,43 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,75 mg/m <sup>3</sup>	Non-applicable

- CONTINUED ON NEXT PAGE -



**ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	101,2 mg/m <sup>3</sup>	67,5 mg/m <sup>3</sup>	67,5 mg/m <sup>3</sup>

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 927-241-2	Oral	Non-applicable	Non-applicable	46 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	46 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	185 mg/m <sup>3</sup>	Non-applicable
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1152 mg/m <sup>3</sup>	640 mg/m <sup>3</sup>	Non-applicable	178,57 mg/m <sup>3</sup>
Solvent naphtha (petroleum), light arom. , < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1152 mg/m <sup>3</sup>	640 mg/m <sup>3</sup>	Non-applicable	178,57 mg/m <sup>3</sup>
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1152 mg/m <sup>3</sup>	640 mg/m <sup>3</sup>	Non-applicable	178,57 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Oral	Non-applicable	Non-applicable	4,51 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	3,25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	8,13 mg/m <sup>3</sup>	Non-applicable
Reaction products of Fatty acids, tall-oil, compds. with oleylamine and Fatty acids, C18-unsatd., trimers, compds. with oleylamine CAS: Non-applicable EC: 942-330-6	Oral	Non-applicable	Non-applicable	0,11 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,21 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,37 mg/m <sup>3</sup>	Non-applicable
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable
	Inhalation	Non-applicable	60,7 mg/m <sup>3</sup>	40,5 mg/m <sup>3</sup>	40,5 mg/m <sup>3</sup>

**PNEC:**

Identification				
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**



Identification				
Reaction products of Fatty acids, tall-oil, compds. with oleylamine and Fatty acids, C18-unsatd., trimers, compds. with oleylamine CAS: Non-applicable EC: 942-330-6	STP	100 mg/L	Fresh water	0,194 mg/L
	Soil	120 mg/kg	Marine water	0,019 mg/L
	Intermittent	0,097 mg/L	Sediment (Fresh water)	29,6 mg/kg
	Oral	0,000416 g/kg	Sediment (Marine water)	2,96 mg/kg
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	STP	200 mg/L	Fresh water	1,1 mg/L
	Soil	0,32 mg/kg	Marine water	0,11 mg/L
	Intermittent	11 mg/L	Sediment (Fresh water)	4,4 mg/kg
	Oral	0,056 g/kg	Sediment (Marine water)	0,44 mg/kg

**8.2 Exposure controls:**



**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

**C.- Specific protection for the hands**





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	37,6 % weight
V.O.C. density at 20 °C:	424,73 kg/m <sup>3</sup> (424,73 g/L)
Average carbon number:	8,95
Average molecular weight:	125,62 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	430 kg/m <sup>3</sup> (430 g/L)
EU limit for the product (Cat. A.I):	500 g/L (2010)
Components:	Non-applicable

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	<input type="checkbox"/> White
Odour:	Solvent
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	157 °C
Vapour pressure at 20 °C:	248 Pa
Vapour pressure at 50 °C:	1629,14 Pa (1,63 kPa)
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	1129,7 kg/m <sup>3</sup>
Relative density at 20 °C:	1,13
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm <sup>2</sup> /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -





Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860**



**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Solubility properties: Non-applicable \*  
 Decomposition temperature: Non-applicable \*  
 Melting point/freezing point: Non-applicable \*

**Flammability:**

Flash Point: 37 °C  
 Flammability (solid, gas): Non-applicable \*  
 Autoignition temperature: 200 °C  
 Lower flammability limit: Not available  
 Upper flammability limit: Not available

**Particle characteristics:**

Median equivalent diameter: Non-applicable

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties: Non-applicable \*  
 Oxidising properties: Non-applicable \*  
 Corrosive to metals: Non-applicable \*  
 Heat of combustion: Non-applicable \*  
 Aerosols-total percentage (by mass) of flammable components: Non-applicable \*

**Other safety characteristics:**

Surface tension at 20 °C: Non-applicable \*  
 Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

- CONTINUED ON NEXT PAGE -

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

**A- Ingestion (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

**B- Inhalation (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

**C- Contact with the skin and the eyes (acute effect):**

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):**

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Solvent naphtha (petroleum), light arom. , < 0.1 % EC 200-753-7 (3); Xylene (3); Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (3); Naphtha (petroleum), heavy alkylate, < 0.1 % EC 200-753-7 (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); ethanol (1); propan-2-ol (3); Hydrocarbons, C9, aromatics (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); Titanium dioxide (2B); Cobalt bis(2-ethylhexanoate) (2B); Xylene (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

**F- Specific target organ toxicity (STOT) - single exposure:**

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

- CONTINUED ON NEXT PAGE -



## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860****SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

Identification	Acute toxicity		Genus
	Route	Toxicity	
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	2000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LD50 oral	15000 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	Non-applicable	
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	3523 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	LD50 oral	2043 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

**Acute Toxicity Estimate (ATE mix):**

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	6124,98 mg/kg (Calculation method)	58,2 %
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

**11.2 Information on other hazards:****Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

**Other information**

Non-applicable

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:****Acute toxicity:**

- CONTINUED ON NEXT PAGE -



**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Concentration		Species	Genus
	LC50			
Hydrocarbons, C9-C10,n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 927-241-2	LC50	>10 - 100 (96 h)		Fish
	EC50	>10 - 100 (48 h)		Crustacean
	EC50	>10 - 100 (72 h)		Algae
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LC50	>1 - 10 (96 h)		Fish
	EC50	>1 - 10 (48 h)		Crustacean
	EC50	>1 - 10 (72 h)		Algae
Solvent naphtha (petroleum), light arom. , < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LC50	>1 - 10 (96 h)		Fish
	EC50	>1 - 10 (48 h)		Crustacean
	EC50	>1 - 10 (72 h)		Algae
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LC50	2200 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1000 mg/L (96 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50	>10 - 100 (96 h)		Fish
	EC50	>10 - 100 (48 h)		Crustacean
	EC50	>10 - 100 (72 h)		Algae
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	LC50	270 mg/L (96 h)	N/A	Fish
	EC50	Non-applicable		
	EC50	Non-applicable		
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	LC50	1300 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	2850 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	53 mg/L (192 h)	Microcystis aeruginosa	Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
	NOEC			
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	NOEC	Non-applicable		
	NOEC	25 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860**



**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Degradability		Biodegradability	
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BOD5	0,19 g O2/g	Concentration	Non-applicable
	COD	0,44 g O2/g	Period	Non-applicable
	BOD5/COD	0,43	% Biodegradable	Non-applicable
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	89,9 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	BOD5	Non-applicable	Concentration	20 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	99 %
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	BOD5	0,25 g O2/g	Concentration	100 mg/L
	COD	2,08 g O2/g	Period	28 days
	BOD5/COD	0,12	% Biodegradable	92 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BCF	
	Pow Log	4
	Potential	
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	BCF	
	Pow Log	2.96
	Potential	

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860**



**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Bioaccumulation potential	
	2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	BCF
	Pow Log	0.56
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
	Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Koc	100	Henry
	Conclusion	High	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Koc	Non-applicable	Henry	2,94E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Non-applicable	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Koc	48	Henry	7,2E-9 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	No
	Surface tension	3,395E-2 N/m (25 °C)	Moist soil	No

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product fails to meet the criteria.

**12.7 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP3 Flammable

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2021 and RID 2021:

- CONTINUED ON NEXT PAGE -



**ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860**

**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Special regulations: 163, 367, 650  
Tunnel restriction code: D/E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**  
Special regulations: 223, 955, 163, 367  
EmS Codes: F-E, S-E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2022:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

- CONTINUED ON NEXT PAGE -



## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860



#### SECTION 15: REGULATORY INFORMATION (continued)

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

##### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

##### Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Decamethylcyclotetrasiloxane, Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

##### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

##### Other legislation:

The product could be affected by sectorial legislation

##### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

#### SECTION 16: OTHER INFORMATION

##### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

##### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

- Removed substances  
2-butanone oxime (96-29-7)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Supplementary information
- Substances contained in EUH208:
  - Removed substances  
2-butanone oxime (96-29-7)

##### Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

H315: Causes skin irritation.

H226: Flammable liquid and vapour.

##### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

##### CLP Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -





## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**ESMALTE JUNOLAC ANTIOX. BLANCO - Código - 4860**



### SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H302 - Harmful if swallowed.  
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Repr. 2: H361d - Suspected of damaging the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1A: H317 - May cause an allergic skin reaction.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.  
STOT SE 3: H335 - May cause respiratory irritation.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

#### Classification procedure:

STOT SE 3: Calculation method  
Aquatic Chronic 3: Calculation method  
Skin Irrit. 2: Calculation method  
Flam. Liq. 3: Calculation method (2.6.4.3)

#### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

#### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
LogPOW: Octanolwater partition coefficient  
Koc: Partition coefficient of organic carbon  
UFI: unique formula identifier  
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -