

Technical Datasheet

FULLCOVER MATT

JUNO

Product Code: 00800 Interior/Trade

ES: Mate Interiores

DESCRIPTION

Fullcover is a breathable flat contract matt emulsion paint based on styrene acrylic resins, titanium oxide and selected fillers, giving excellent opacity and whiteness.

USE: INTERIOR

Fullcover is an economical quality contract matt emulsion. Provides excellent coverage and dries to an outstanding opacity on interior walls and ceilings leaving a permeable breathable finish. Ideal for use as a base coat on new plaster or plasterboard where a flat matt opaque finish is required. Also suitable for use on aged plaster, wall boards, concrete, cement rendering, brickwork and internal blockwork.

PROPERTIES

- High opacity/hiding power.
- Trade/Contract properties for efficient use.
- High solids volume level allowing for thicker coating after application
- Excellent practical coverage
- Ideal for a variety of surfaces
- Breathable
- Quick drying
- Euroclass Fire retardant certified

APPROVAL CERTIFICATIONS

- Reaction to fire: Euroclass B-s1, d0. UNE 13501-1
Certified under branding name: Mate Interiores

**Finish:** Matt**Colour:** White**Viscosity:** 20000 ± 3000 cp**Density:** 1,77 ± 0,05 g/cc -**Solids in volume:** 58% (± 2%)**Drying:** Touch dry 1 hour**Min. Repaint time:** 3-4 hours**Max. Repaint time:** Unlimited**Thinner:** Water (Dilute max. 5-20% - More info below)**Practical Coverage:** 8-10 m²/L (Per coat for 50 dry microns)
Average consumption, depending on substrate absorption and texture.**Tinting:** Juno Universal colourant (max. 3%)**Flash point:** Not flammable**VOC Content:** Máx. 30 g/l

00800 WHITE



Format: 15 L

Store paint in dry conditions and protected from extreme cold or warm temperatures and away from direct sunlight. (Optimal conditions between 5 – 35°C.) Provided optimal conditions recommended storage time is 24 months.

The information contained in this data sheet may change and must be updated. Consult www.junopaints.com or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through trials, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, employment and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or manipulator of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.

Technical Datasheet

FULLCOVER MATT



Product Code: 00800 Interior/Trade

ES: Mate Interiores

SURFACE PREPARATION

UNTREATED SURFACE. On new, firm, clean and dry surfaces, no preparation of the substrate is necessary. For added consistency and dustproofing, prime with a coat of diluted Hidrocril Sealer (Prod.Code 81.006) (1 part Hidrocril : 4 parts Water).

On projected plasters, due to varying levels of absorption it is recommended to seal the surface applying 1 coat of **Aquasell (Prod.Code 21.203)**.

PAINTED SURFACES. If the paint is in good condition, apply the product directly. For paint in poor condition, remove loose flaking paint, dust and dirt. Go over defective areas, repairing cracks and irregularities with **Juno Repair Plaster (Prod.Code 77.000)** before painting.

Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Paint out a small test patch to check the strength and adhesion of the paint and to prevent possible incompatibilities with previous coats/applied paints.

PATHOLOGIES

Mould contamination. Wash mould stains thoroughly and disinfect using **Junoclean Anti-Mold wash (Prod.Code 760.180)**. Rinse with clean water and let dry completely. Coat using paint with anti-mold additive or add JUNO's **Misky-Misky anti-mould additive (Prod.Code 79.597)**.

Saline Efflorescence. Brush thoroughly, clean and neutralize with a Chloridic acid or Zinc Sulphate solution (to 10%). Rinse with water and allow to dry completely before painting.

Moisture, grease, smoke or nicotine stains, etc. Clean with water and suitable detergent. Leave to dry completely before applying and priming with **Tapa-Manchas Stain Cover. (Prod.Code 21.350)**.

APPLICATION TIPS

Stir paint thoroughly until complete homogenization. Ensure good ventilation during application and drying.

Do not breathe spray. Wear respiratory protection.

Apply on surfaces that are consistent, clean, completely dry, free from efflorescence (saltpeter) and mould.

Do not apply on surfaces with a temperature below 5°C, nor excessively warm surfaces. Maximum relative humidity 85%.

The need to dilute the product depends on porosity and state of the surface. If more than one can of a colour is to be used in the same area, intermix before use.

It is advisable to protect areas that are not going to be painted (plugs, skirting boards, floors, door frames and windows) with painter's tape and paper. Once the work is completed, remove the tape before the paint completely dries, to prevent paint from being pulled off.

APPLICATION METHOD. Brush, roller or spray equipment. Apply minimum two coats of FULLCOVER when used as a topcoat.

Product can be thinned out 10-20% on first coats and 5-10% for topcoats if required.

Apply on primed consistent, dry and clean surfaces free of dust, efflorescence, oxides, grease, wax etc.

APPLICATION - NEW SURFACES: On masonry, apply a 10% thinned coat. On powdery plasters

apply a coat of lime based primer or suitable sealer. For finishing always apply two coats of Fullcover.

APPLICATION - PAINTED SURFACES: If the existing paint is in good condition, clean and apply two coats of Fullcover. If the surface is in poor condition, remove existing paint and proceed as for new surfaces.

CLEANING. Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Do not empty product into drains or watercourses.

SAFETY AND ENVIRONMENT

Minimize product waste by estimating the amount needed, taking into account the m², porosity and texture of the support. Store any excess material in a ventilated and dry place. The container must be clean and of adequate size for the amount of product left over. Close containers carefully and keep upright to avoid spills. Preserve the containers away from frost, high temperatures and direct exposure to the sun.

Recover any unused paint for future use and to reduce environmental effects.

Do not eat, drink or smoke during the preparation and application of the product. Surface preparation and application operations must be carried out with the corresponding safety measures. For more information, consult the Safety Data Sheet.

In case of contact with eyes wash with clean and abundant water. Keep out of the reach of children.

Do not discharge into drains or the environment. Dispose of at an authorized waste collection point. Consult your town hall for correct recycling method for container and waste/leftovers paint according to local legislation and principles of environmental respect.

The information contained in this data sheet may change and must be updated. Consult www.junopaints.com or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through trials, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, employment and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or manipulator of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.