

## MULTIPLAST SEALING PUTTY

**Product Description** Acrylic putty in aqueous phase for sealing cracks and fissures.

**Classification** G3E5S2V2W2A0C0 according to UNE 48313:2008 EX standard

### Technical features

|                                                                    |                                                                                                                           |
|--------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>Fire behaviour</b>                                              | D2 s2 d0                                                                                                                  |
| <b>Granulometry</b>                                                | 200 microns                                                                                                               |
| <b>pH</b><br>S/ITE CI/18-L                                         | 8.0 - 8.5                                                                                                                 |
| <b>In depth drying time (1mm thickness)</b><br>S/ITE CI/52-L       | 12 hours                                                                                                                  |
| <b>Adherences</b><br>On concrete, brick, wood and plaster surfaces | >0.5 MPa                                                                                                                  |
| <b>Performance</b><br>In 1 cm wide cracks                          | 50 - 70 g/m linear                                                                                                        |
| <b>Recommended storage time</b>                                    | Twelve months in original, unopened container, at normal temperature and humidity. Store in premises protected from frost |
| <b>VOCs (g/l)</b><br>UNE EN ISO 11890-1                            | 41.53 g/L                                                                                                                 |

WATER-BASED ANTI-STAIN PLIOTIX ECOBARP 1/2

## Application instructions

|                                   |                                                                                                                               |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>Application on</b>             | Acrylic sealant putty for general use. Ideal for sealing shutter boxes, cracks, low motion joints, mouldings and door frames. |
| <b>Surfaces</b>                   | Plaster, gypsum, cement, brick, stone, wood, concrete, aerated concrete, semi-absorbent surfaces.                             |
| <b>Maximum thickness per coat</b> | 10 mm                                                                                                                         |

**Cleaning of utensils** Clean with water immediately after.

## Properties and Instructions for use

### Properties:

Can be coated by all types of conventional paints after complete drying

Extra-white.

Applicable on thickness.

Excellent thixotropy.

Flexible.

Great adhesion.

Repairs cracks, fissures and micro-fissures between materials of a different nature.

### Instructions for use:

Surfaces must be intact, dry, cohesive, absorbent and well adhered.

Product ready for use.

Apply directly on cracks and fissures.

## General

|                  |                                                         |
|------------------|---------------------------------------------------------|
| <b>Packaging</b> | 310 mL cartridge                                        |
| <b>Storage</b>   | Store in a cool place.<br>Do not store open containers. |

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For these reasons, we cannot accept any undesired consequence deriving from its use. 20-04-2016 This sheet replaces all previous versions.