

DOUGLAS WHITE SATIN PAINT

Douglas White Satin Paint provides a soft low-sheen finish on interior woodwork (doors, skirting, balustrades etc) as well as external gates and railings.

HEALTH&SAFETY

Paint product UN 1263

Hazardous ingredients: solvent naphtha (petroleum), medium aliph.; solvent naphtha (petroleum), medium aliph.; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Get medical advice/attention if you feel unwell.

EUH208 - Contains 2-butanone oxime (96-29-7), cobalt(II) 2-ethylhexanoate (136-52-7). May produce an allergic reaction. EUH210 - Safety data sheet available on request. EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Any disposal practice must be in compliance with national laws and regulations. Do not dump into any sewers, on the ground, or into any body of water. Dispose of contents/container to hazardous or special waste collection point.

WARNING



PREPARATION

Ensure the surface is clean, dry and free from any wax, oil, grease and dirt. Remove any loose and flakey material and sand surface smooth with fine sandpaper. Remove all signs of rust to a clean bright surface. On new unpainted surfaces, prime with an appropriate primer.



APPLICATION

Paint should be stirred thoroughly before use. Apply by brush, roller or spray. For best results apply a minimum of two coats. No thinning is necessary but, if required, thin by up to 10% with Douglas White Spirits.



COVERING CAPACITY

Approximately 10 square metres per litre depending on the porosity of the surface.

DRYING TIME

Surface dry in 3 hours. Allow to dry overnight between coats. The layer thickness of the paint and the temperature affect the drying time.

CLEAN UP

Remove as much product from equipment as possible before washing with Douglas white spirit. Do not empty product into drains or waterways. Some local authorities have special facilities for disposal of waste coatings.

**EU limit value for this product (Cat:A/d): 300g/l.
This product contains a maximum of 300g/l VOC.**



CURUST INDUSTRIES LTD

Unit 7, Bromley Business Park,
Greystones, Co. Wicklow

Tel: (01)2760800

info@curust.ie, www.curust.ie

500ml e

Douglas
DECORATIVE RANGE

WHITE SATIN PAINT

SUPERIOR LOW SHEEN FINISH



**SOLVENT
BASED**

WHITE SATIN FINISH

WHITE SATIN PAINT:

- **SUITABLE FOR BOTH
INTERIOR AND
EXTERIOR USE**
- **AN ATTRACTIVE
HARDWEARING WHITE
SATIN FINISH**
- **CAN BE USED ON BOTH
WOOD AND METAL**