DOUGLAS UNDERCOAT

Douglas Undercoat provides the ideal foundation prior to painting. It has excellent obliteration properties covering marks and light stains. It is recommended for use beneath gloss and semi-gloss finishes. Suitable for interior and exterior use on wood, metal, plaster and all normal surfaces for a perfect finish.

PAINT PRODUCT 1263

Hazardous ingredients: Solvent naphtha (petroleum), medium aliph.; Solvent naphta(petroleum), medium aliphatic(Hydrocarbons, C9-C12, n-alkanes, iso alkanes, cyclic, aromatics(2-25%); solvent naphtha(petroleum), medium aliph.

Flammable liquid and vapour. May cause damage to organs (lungs) through prolonged or repeated exposure (if inhaled). Harmful to aquatic life with long lasting effects.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.No smoking. IF SWALLOWED: Immediately call doctor; a POISON CENTER. If medical advice is needed, have product container or label at hand. Keep out of reach of children.

EUH208 - Contains 2-butanone oxime(96-29-7), cobalt(II) 2-ethylhexanoate(136-52-7). May produce an allergic reaction.

WARNING



DURABLE

1-4 HOURS QUICK DRYING

STIR WELL

PRERARATION

Ensure the surface is clean, dry and free from grease, oil, wax and powdery deposits etc. by wiping with a cloth dampened with Douglas White Spirits. For best results prime new and bare areas with the appropriate Douglas Primer followed by a coat of Douglas Undercoat. If applying to wood, ensure all knots are sealed with Douglas Patent Knotting.

APPLICATION

Paint should be stirred thoroughly before use. Apply by brush or spray.

COVERING CAPACITY

10 square metres/litre per coat.

DRYING TIME

Touch dry in 4-6 hours in good conditions. Allow to dry overnight between coats.

CLEAN UP

Remove as much product as possible from the application equipment before washing in Douglas Brush Cleaner or Douglas White Spirits. Do not empty product into drains or waterways. Dispose of this material and container at hazardous or special waste collection point.

EU limit value for this product (Cat: A/i) : 500g/l.
This product contains a maximum of 500 g/l VOC.

CURUST INDUSTRIES LTD.
Units 12 & 13, Southern Cross Business Park,
Bray, Co. Wicklow, Ireland.
Tel: +353 1 276 0800. Fax: +353 1 276 0799.
email: info@curust.ie www.curust.ie

500ml e

Douglas DECORATIVE RANGE

UNDERCOAT

HIGH PERFORMANCE UNDERCOAT FOR USE OVER WOOD, PLASTER, PRIMED JOINERY & METAL



- **HIGH BUILD UNDERCOAT WITH EXCELLENT OBLITERATION PROPERTIES**
- **GREAT AS AN 'INTERMEDIATE COAT' BETWEEN PRIMER AND FINISHING COATS**
- **INTERIOR AND EXTERIOR USE**
- **SUITABLE OVER WOOD, METAL, PLASTER AND MOST OTHER SURFACES, ONCE SUITABLY PRIMED**
- **IDEAL AS AN UNDERCOAT FOR DOUGLAS ENAMEL GLOSS PAINT**