BRICK & TILE PAINT

PAINT UN 1263

Contains: HYDROCARBONS, C9-C11, <2% AROMATICS

Flammable liquid and vapour. May cause drows iness or dizziness. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Avoid breathing vapours/ spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents/ container in accordance with national regulations. Repeated exposure may cause skin dryness or cracking.

EU limit for this product (Cat A/c) 430g/l (2010). This product contains a maximum of 430g/l VOC.





WARNING



PREPARATION

Ensure the surface is clean, dry and free from any wax, oil, grease and dirt.

APPLICATION

Paint should be stirred thoroughly before use. Brush, roller or spray directly to surface.

COVERING CAPACITY

Approximately 10 square metres per litre depending on the porosity of the surface.

DRYING TIME

Surface dry in 3 hours. Allow to dry overnight between coats.

CLEAN UP

Remove as much product from equipment as possible before washing with Douglas white spirit. Do not empty product into drains or waterways. Some local authorities have special facilities for disposal of waste coatings.

CURUST INDUSTRIES LTD.
Unit, 7, Farankelly, Rd., Bromley Bus.Park, Greystones, Co. Wicklow
Tel: +353 1 276 0800. Fax: +353 1 276 0799. email: info@curust.ie www.curust.ie