

DOUGLAS ALUMINIUM PAINT

Douglas Aluminium Paint gives a durable brilliant silver-like finish to a wide range of surfaces. It is resistant to the effects of heat and water and can effectively reduce temperatures when applied to storage tanks, caravan roofs etc.

HEALTH & SAFETY

Paint product UN 1263

DANGER

Contains: Solvent naphtha (petroleum), medium aliph.

Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wash hands, forearms and face thoroughly after handling.

Do not eat, drink or smoke when using this product.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH208 - Contains Neodecanoic acid, cobalt salt(27253-31-2).

May produce an allergic reaction.

Any disposal practice must be in compliance with national laws and regulations.

Do not dump into any sewers, on the ground, or into any body of water.

Dispose of contents/container to hazardous or special waste collection point.



PREPARATION

Ensure the surface is clean, dry and free from any wax, oil, grease and dirt. Remove any loose and flakey material by wire-brushing where necessary.



APPLICATION

Paint should be stirred thoroughly before use. Open carefully, preferably shielded under rags as there may be a build up of pressure during storage. Suitable for applying by brush or spray.



COVERING CAPACITY

8 - 10 Sq metres per litre depending on the porosity of the surface.

DRYING TIME

Surface dry in 3 hours. allow to dry overnight between coats.

CLEAN UP

Remove as much product from equipment as possible before washing with Douglas white spirit. Do not empty product into drains or waterways. Some local authorities have special facilities for disposal of waste coatings.

EU limit value for this product (Cat: A/i): 500g/l.
This product contains a maximum of 500g/l VOC.



CURUST INDUSTRIES LTD.

Unit 7, Bromley Business Park,
Farankelly Rd., Greystones, Co. Wicklow.

Tel (01) 2760800

info@curust.ie www.curust.ie

500ml e

Douglas
DECORATIVE RANGE

ALUMINIUM PAINT

A BRILLIANT DECORATIVE FINISH



SOLVENT
BASED

BRIGHT ALUMINIUM

EXTRA BRIGHT ALUMINIUM PAINT:

• INTERIOR &
EXTERIOR USE

• FOR USE ON WOOD OR
METAL

• REFLECTS HEAT
FROM SURFACES

• HEAT RESISTANT TO 150°C