


2K PRE FILLED CANS

OUR 2K SPRAY CANS ARE PREPARED WITH PROPELLANT GAS, SOLVENTS AND ORIGINAL HARDENER IN A SEPARATE PRE-FILLED CARTRIDGE. THE MIXING OF THE 2K TOPCOAT WITH THE ORIGINAL HARDENER ACHIEVES AN OPTIMAL QUALITY WITH RESPECT TO GLOSS, CURING, WEATHER AND CHEMICAL RESISTANCE. SIMPLE, TIME-SAVING APPLICATION. EXCELLENT ATOMISATION. LIGHT BLENDING.

SUITABLE SUBSTRATES

SOLVENT OR WATER BASED BASECOAT PAINT

APPLICATION DATA




DEPENDING ON CONSISTENCE AND COLOUR OF THE GROUND: 400ML IS SUFFICIENT FOR APPROX. 0.8M




DEPENDS ON SURROUNDING TEMPERATURE, AIR HUMIDITY & THICKNESS OF THE APPLIED COAT & FILLED TYPE OF PAINT


APPLICATION METHOD



BEFORE USE, SHAKE THE AEROSOL FOR 2 MINUTES & SPRAY A SAMPLE AREA



APPLY IN CROSS COATS FROM A DISTANCE OF 250MM FROM OBJECT



AFTER USE TURN AEROSOL UPSIDE DOWN, PRESS THE NOZZLE FOR APPROX. 5 SEC & CLEAR VALVE



2K PRE FILLED CANS

TECHNICAL DATA

CHEMICAL BASE	ACRYLIC
VOC CONTENT	305G / 400ML
COVERAGE	0.30 - 0.40M2
STORAGE NOTES	EMPTY CANS AT 36 MONTHS. POT LIFE FILLED CANS APPROX. 12 HOURS (10°-25°C, RELATIVE AIR HUMIDITY OF MAX. 60%)

DISPOSAL

COMPLETELY EMPTIED CANS SHOULD BE PUT IN RECYCLING SKIPS OR APPROPRIATE CONTAINER. CANS WHICH ARE NOT EMPTY SHOULD BE DISPOSED OFF AS SPECIAL REFUSE.

THIS APPLICATION AND TECHNICAL INFORMATION IS GIVEN TO THE BEST OF OUR KNOWLEDGE. THE NOTES MENTIONED HEREIN ARE, HOWEVER, NON-BINDING AND DO NOT EXEMPT YOU FROM OWN TESTS TO SEE WHETHER THE PRODUCTS SUPPLIED BY US ARE SUITABLE FOR YOUR SPECIAL APPLICATION. THE USE AND PROCESSING IS BEYOND OUR CONTROL AND THEREFORE EXCLUSIVELY IS THE RESPONSIBILITY OF THE USER.

NEED HELP? VISIT OUR WEBSITE FOR MORE OR SEND US AN EMAIL

WWW.VINNYBYRNE.COM

INFO@VINNYBYRNE.COM

