

THERMAL SUPER GRIP GLOVES (LARGE) PACK OF 6 PAIRS

MODEL NO: TSP126/6



Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.



REFER TO INSTRUCTIONS

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.

1. INTRODUCTION

Nitrile coated palm gives superior grip and dexterity. Good abrasion resistance. Breathable open back. CE Marked and conforms to BS EN 388:2016 2-2-4-2-X.

Sizes: TSP126/6 (Large)
Notified Body: 0075

Type Examination Certificate Number: 0075/1022/162/10/19/3084

Carried Out By: CTC

2. SAFETY

- ✓ Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.
- ✓ This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.
- √ The protection against risks or hazards which are not mentioned in this document is not warranted.
- ✓ The levels of performance mentioned are only valid for the palm of the glove.(7G Polyester terry liner;black foam latex coated on palm.
- ✓ These levels of performance are obtained from the tests done according to the conditions defined by the applicable standards.
- ✓ This glove shall not be in contact with fire.
- ✓ The gloves should be inspected before each use, and replaced if damaged.
- ✓ For gloves with two or more layers of material, the performance levels are warranted only for the whole glove.
- ✓ For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

3. APPLICABLE STANDARDS



Abrasion Resistance	2	(on 4 maxi)
Blade Cut Resistance	2	(on 5 maxi)
Tear Resistance	4	(on 4 maxi)
Puncture Resistance	2	(on 4 maxi)
Cut Resistance Method (EN ISO 13997)	Х	(A to F)
Impact Protection	-	

'X' indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

4. MAINTENANCE

4.1. STORAGE

- ✓ Store the gloves in their original packaging,in normal temperature and humidity conditions in clean ventilated premises.
- ✓ When stored in appropriate conditions, performance of this product will not be significantly reduced.
- ✓ The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated light.

5. OBOLESCENCE

The design performance is not significantly affected by ageing when stored in an appropriate conditions (humidity,clean,ventilated light).

This document has been drawn up according to Regulation (EU) 2016/425 as amended to apply to GB for Personal Protective Equipment. The declaration of conformity can be accessed at www.sealey.co.uk.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



URCHASE HERI

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. **Important**: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.