

Douglas

DECORATIVE RANGE

OXIDE PAINT

LONG LASTING ANTI-CORROSIVE GLOSS PAINT WITH A HIGH QUALITY ALKYD RESIN FINISH



• INDUSTRIAL AND AGRICULTURAL USE

• EXCELLENT COVERING POWER ON ALL TYPES OF SUBSTRATES

• INTERIOR AND EXTERIOR USE

• SUITABLE FOR USE OVER BLOCKWORK, STEEL SHEETS, ASBESTOS SHEETING OR WOOD

• PROTECTS AGAINST WEATHERING AND CORROSION

• LEAD AND CHROME FREE

DANGER

Hazardous ingredients: solvent naphtha(petroleum), medium aliph; cobalt(II) 2-ethylhexanoate

Flammable liquid and vapour. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage.



PREPARATION

Ensure the surface is clean, dry and free from any wax, oil, grease and dirt. Remove any loose and flakey material before applying product. On new unpainted surfaces it may be necessary to prime first with a suitable primer. If going straight onto galvanised metal be sure to prepare the surface with a mordant solution or suitable primer in advance of applying paint.



APPLICATION

Douglas Oxide Paint can be used as a single-coat general purpose protective coating on any type of normally prepared surface. It is a high performance coating made from synthetic resins, formulated for ease of use by spray, brush or roller. Paint should be stirred thoroughly before use taking care to mix the paint at the bottom of the tin. Supplied ready for use but, if necessary, thin with Douglas White Spirits.



COVERING CAPACITY

Approximately 10 square metres per litre.

DRYING TIME

Surface dry 3- 6 hours. Allow to dry overnight if applying more than one coat.

CLEAN UP

Remove as much product from equipment as possible before washing with Douglas White Spirits. Do not empty into drains or waterways. Some local authorities may have special facilities for disposal of waste coatings.

EU limit for this product (Cat: A/i) is 500g/l. This product contains a maximum of 500g/l VOC.



**CURUST
INDUSTRIES
LTD.**

Units 12 & 13,
Southern Cross
Business Park,
Bray, Co. Wicklow,
Ireland.

email: info@curust.ie
www.curust.ie

e **2.5Ltr**