

DOUGLAS ENAMEL GLOSS PAINT

Specially formulated to provide a long-lasting high-gloss finish to doors, gates, railings and windows etc. Suitable for interior and exterior use on wood, metal and most other surfaces.

HEALTH&SAFETY Paint product UN 1263. Hazardous ingredients: Solvent naphtha (petroleum), medium aliphatic (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatics (2-25%) Flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects. Wear protective gloves, eye protection. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Do not breathe vapours. Do not get in eyes, on skin, or on clothing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. EUH208 - Contains 2-butanone oxime (96-29-7). May produce an allergic reaction.

DANGER



PREPARATION

Remove any loose particles and clean away any scale, grease and dirt. If applying to metal, prime first with a suitable metal primer (eg Lowe Rust Primer). For best results use appropriate Douglas Undercoat after priming. Allow to dry overnight before applying Douglas Enamel Gloss Paint. If painting onto wood, seal any knots first with Douglas Patent Knotting.

APPLICATION

Paint should be stirred thoroughly before use. Apply by brush, roller or spray. Apply 1-2 coats.

COVERING CAPACITY

Coverage is approx. 13 square metres/litre per coat.

DRYING TIME

Touch dry in 4-6 hours in good conditions. Allow to dry overnight between coats. Application works must be carried out at ambient temperature above +10C and relative humidity below 80%.

CLEAN UP

Remove as much product as possible from the application equipment before washing in Douglas Brush Cleaner or Douglas White Spirits. Do not empty product into drains or waterways. Dispose of this material and container at hazardous or special waste collection point.

EU limit value for this product (Cat:A/d): 300g/l.
This product contains a maximum of 300g/l VOC.



CURUST INDUSTRIES LTD.

Units 12 & 13,
Southern Cross
Business Park,
Bray,
Co. Wicklow, Ireland.
Tel: +353 1 276 0800.
Fax: +353 1 276 0799.
email: info@curust.ie
www.curust.ie

250ml e

Douglas
DECORATIVE RANGE

SOLVENT
BASED



ENAMEL
GLOSS PAINT

BLACK

HANDY GLOSS PAINT

ENAMEL GLOSS PAINT:

- FOR INTERIOR AND EXTERIOR USE
- A HIGH BUILD HARD- WEARING SMOOTH GLOSS PROTECTIVE FINISH
- IDEAL FOR WOOD, METAL, PLASTER AND MOST OTHER SURFACES, ONCE SUITABLY PRIMED
- LONG LASTING FINISH
- TOUGH AND DURABLE