

BOILED LINSEED OIL

500ml e

Douglas Boiled Linseed Oil is ideal for most bare woods with the exceptions of oak and teak. It protects the wood from drying out after long periods in the sun. It gives the surface an attractive ruby tint and a light gloss finish.

Directions for use: Wipe the surface with a cloth dampened with White Spirit to remove any grease or dirt. Treat any mildew etc. with Fungicidal Wash. Apply Boiled Linseed Oil liberally by either brushing or using a cloth. Remove excess linseed oil after saturation. For best results apply 2 or 3 coats allowing 24 hours between coats. To avoid the risk of spillage always ensure that the cap is secure and the container is held upright during transportation and storage.

HEALTH & SAFETY

Keep out of reach of children.

Not to be taken internally.

In case of contact with skin, wash immediately with soap and water or a proprietary skin cleaner.

In case of contact with eyes, rinse immediately with plenty of water and if necessary, seek medical attention.

Brushes should be cleaned with Douglas White Spirits and then washed in warm soapy water.

In common with most Linseed Oil based products, soiled application cloths should not be left where they may constitute a fire hazard as they can be liable to spontaneous combustion, ie self-igniting without warning.

Immediately after use, saturate all soiled application cloths with water and dispose of safely outside.

Dispose of the contents/container to a hazardous waste collection point.

Douglas
DECORATIVE RANGE

Curust Industries Ltd.
Southern Cross Business Park,
Bray, Co. Wicklow, Ireland.
Tel: +353 1 2760800
Email: info@curust.ie



R1