DANISH OIL 1Ltr ℮

A blend of rich oils, including Tung Oil, providing an attractive water repellent low lustre natural finish to woods. Suitable for interior and exterior use including doors, panelling, furniture, wood decorations and woodturning.

Instructions

• Shake well before use. • Carry out a small test patch first to determine an acceptable finish on an off-cut or unseen area. • Ensure surfaces to be treated are uncoated, dry and clean - free from wax/dirt. • Oily woods require wiping with white spirit before application. • Apply liberally with a lint-free cloth or brush. • Leave for 10-15 minutes then remove excess with a clean lint-free cloth. • Apply a minimum of 2 coats internally on new wood allowing 6-10 hours between coats. • Previously oiled wood can be partially sealed, especially if a slight gloss is evident, that prevents any fresh application of oil to penetrate. • To prepare the wood surface use a very fine stainless steel wool lightly rubbing in the direction of the grain and wipe with white spirit to remove residues prior to re-application of oil. • For exterior you apply a minimum of 3 coats ensuring any end grain wood is thoroughly treated. • Exterior wood will require regular re-oiling. • Allow minimum 24 hours to fully dry during which time protect from water. • Ideally apply between 10-25 Celsius, do not apply when ambient or surface temperature below 5 Celsius. • Coverage 6 to 10 m² per litre depending upon would porosity. • Clean brushes while wet with white spirit.

Precautions

• Clothes used for oiling may spontaneously combust, immediately after use soak them in soapy water and then lay them flat outside on a non-combustible surface to dry.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Contains: hydrocarbons, C9-C11 , n-alkanes, isoalkanes, cydics, <2% aromatics; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cydics, aromatics (2–25%); Naphtha (petroleum), hydrotreated heavy.

UFI: 1220-1075-YOOF-9VPQ

DANGER



HAZARD STATEMENTS

• Flammable liquid and vapour • May be fatal if swallowed and enters airways • May cause drowsiness or dizziness • Keep out of reach of children • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking • Keep container tightly closed • Avoid breathing fumes, vapours, mist, spray • Use only outdoors and in a well ventilated area • Wear eye protection, face protection, protective clothing, protective gloves • Dispose of contents/container in accordance with local/regional/national/international regulations • Repeated exposure may cause skin dryness or cracking

VOC statement: EU limit value for this product: 750g/litre(2010). This product contains max 536g/litre.

Douglas DECORATIVE RANGE

CURUST INDUSTRIES LTD.

Unit 7, Bromley Business Park, Greystones, Co. Wicklow, Ireland.
Tel (01) 2760800 info@curust.ie www.curust.ie

5 098929 011585