SAFETY DATA SHEET

SHELLAC SANDING SEALER

Compilation date: 17/07/2011

Revision date: 09/03/2018

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SHELLAC SANDING SEALER

Product code: DASS0250

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Foundation coat / sealer

1.3. Details of the supplier of the safety data sheet

Company name: Curust industries Ltd

Unit 7, Bromley Business Park

Greystones

Co. Wicklow

Tel: 01 2760800

Email: sales@curust.ie

1.4. Emergency telephone number

Emergency tel: 01 8092166

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Flam. Liq. 2: H225

Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

[cont...]



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P264: Wash contaminated skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

P403+235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container to national regulations.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHANOL - REACH registered number(s): 01-2119457610-43-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-578-6	64-17-5	-	Flam. Liq. 2: H225	70-98%

METHANOL - REACH registered number(s): 01-2119433307-44-XXXX

200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Get medical attention promptly if symptoms occur after washing.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious,

[cont...]

ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If unconscious, check for breathing and apply artificial respiration if necessary. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. May cause drowsiness. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. There may be drowsiness, slurred speech, muscular weakness, muscle twitching, tremor, blurred vision, dilated pupils and shock.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Use water spray to cool containers. Suitable extinguishing media for the surrounding fire should be used. Water fog. Alcohol resistant foam. Dry chemical powder. Sand. Dolomite or other inert material. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. Forms explosive air-vapour mixture. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Contain the spread of the firefighting media. Do not allow run-off from firefighting to enter drains or water courses.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

[cont...]

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air. Static electricity and formulation of sparks must be prevented.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ETHANOL

Workplace exposure limits: **Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m3	-	-	-

METHANOL

UK	266 mg/m3	333 mg/m3	-	-

DNEL/PNEC Values

Hazardous ingredients:

ETHANOL

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	1900 mg/m3	Workers	Local
DNEL	Dermal (repeated dose)	343 mg/kg/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	95 mg/m3	Workers	Systemic
DNEL	Inhalation	950 mg/m3	Consumers	Local
DNEL	Dermal (repeated dose)	206 mg/kg/day	Consumers	Systemic
DNEL	Inhalation (repeated dose)	114 mg/m3	Consumers	Systemic

[cont...]

DNEL	Oral (repeated dose)	87 mg/kg/day	Consumers	Systemic
PNEC	Fresh water	0.96 mg/l	-	-
PNEC	Marine water	0.79 mg/l	-	-
PNEC	Sediment	3.6 mg/kg	-	-
PNEC	Soil (agricultural)	0.63 mg/kg	-	-

METHANOL

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	260 mg/m3	Workers	Systemic
DNEL	Inhalation	260 mg/m3	Workers	Systemic
DNEL	Inhalation (repeated dose)	260 mg/m3	Workers	Local
DNEL	Inhalation	260 mg/m3	Workers	Local
DNEL	Inhalation (repeated dose)	50 mg/m3	General Population	Systemic
DNEL	Inhalation	50 mg/m3	General Population	Systemic
DNEL	Inhalation (repeated dose)	50 mg/m3	General Population	Local
DNEL	Inhalation	50 mg/m3	General Population	Local
DNEL	Dermal (repeated dose)	40 mg/kg bw/day	Workers	Systemic
DNEL	Dermal	40 mg/kg bw/day	Workers	Systemic
DNEL	Dermal (repeated dose)	8 mg/kg bw/day	General Population	Local
DNEL	Dermal	8 mg/kg bw/day	General Population	Local
DNEL	Oral (repeated dose)	8 mg/kg bw/day	General Population	Systemic
DNEL	Oral	8 mg/kg bw/day	General Population	Systemic
PNEC	Fresh water	20.8 mg/l	-	-
PNEC	Fresh water sediments	77 mg/kg	-	-
PNEC	Marine water	2.08 mg/l	-	-
PNEC	Marine sediments	7.7 mg/kg	-	-
PNEC	Microorganisms in sewage treatment	100 mg/l	-	-
PNEC	Soil (agricultural)	100 mg/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Contact lenses should not be used when working with htis chemical. Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing. Ensure safety shower is to hand.

Environmental: Avoid release to the environment

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Brown

[cont...]

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: 1.22 cP @ 20oC

Boiling point/range°C: 78

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: 12 cc

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 0.79

pH: No data available.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Flames. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg

[cont...]

ORL	RAT	LD50	7060	mg/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. May cause drowsiness. May cause dizziness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. There may be drowsiness, slurred speech, muscular weakness, muscle twitching, tremor, blurred vision, dilated pupils and shock.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ETHANOL

Salmo Gairdneri	96H LC50	13000	mg/l

METHANOL

BLUEGILL (Lepomis macrochirus)	96H LC50	15400	mg/l
Daphnia magna	48H EC50	> 10000	mg/l
Salmo gairdneri	96H LC50	10800	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

[cont...]

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Avoid release to the environment.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Disposal of contaminated packaging as unused product unless fully cleaned.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No **Marine pollutant:** No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

[cont...]

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.