

TECHNICAL DATA SHEET**Product name: Polifur 777 Light Weight Body Filler x1050****1. Properties:**


It has excellent filling and bonding strength with unsaturated polyester resin. Due to its low density, it can be used for filling deep dent or scratches in different industries.


Suitable for use on:

- Steel
- Galvanized steel
- Aluminum

- Free pinhole
- No cracking and shrinking
- Density: $1,38 \pm 0,02$ gr/ml

2. Application:

	Degrease and sand the surface	
	Degrease with silicone degreaser	
	Polifur Light Weight Putty B.P.O. Hardener	100 gr 2-3 gr
	20°C Application life (pot-life)	4-8 min.

	20°C Drying time	20-40 min.
	Rough sand	P-80 / P-180
	Dry sanding with Orbital sander	P-180 / P-280

3. Storage conditions and shelf life:**3. Storage conditions and shelf life:**

Store in a dark and cool place away from fire and heat sources. The shelf life in unopened original package in the temperature of 20°C is 18 months.

4. Color:

Grey, Yellow

5. Other information:

For professional use only. This technical data sheet is supplied for informational purposes only! The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. We are not responsible for the results obtained by others over whose methods we have no control and thereof we are not liable for consequential or incidental damages including loss of profits. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.