

Product Information | TECHNICAL DATA SHEET

ULTRALIGHT FILLER

500g / 17,64 oz

GENERAL DESCRIPTION

Two-component low-density polyester filler, specially developed for repairs and filling work that must add the minimum possible weight to the repaired surface.

Its ultralight formulation, combined with a creamy consistency and excellent workability, allows fast, simple and comfortable application, even on large surfaces.

It is a solution especially suited to professionals and users looking for a lightweight filler that is easy to apply and quick to work with, while maintaining a good balance between performance and ease of use.

DIRECTIONS FOR USE

- Prepare the surface so that it is dry, clean and free from dust, grease, dirt, rust and poorly adhered paint residues.
- Apply a line of hardener across the whole portion of filler (100:2 ratio). Mix thoroughly until a homogeneous paste and a uniform colour are obtained.
- Allow to dry for 30 min at a temperature of 20 °C. Drying time depends on the ambient temperature. High temperatures speed up curing.
- Sand first with P80-P120 abrasive paper and continue with P180-P240 for the finish. For high-quality finishes, use finer grits.
- Before the final finish, check that the repair is completely hardened.
- Clean the spatulas with MTN WEPRO Cleaning Solvent or a universal cleaning solvent before the product hardens.

PHYSICAL PROPERTIES

Colour:	White
Nature:	Unsaturated polyester
Specific weigh:	1.00-1.06 g/cm³
VOC:	164 g/L
Working time after mixing with hardener	
	3 min at 30°C
	5 min at 20°C
	11 min at 10°C
Drying time:	
	15-20 min at 30°C
	20- 25 min at 20°C
	30-40 min at 10°C
Full cure:	Approximately 2 hours (20 °C)
Recommended sanding:	P80 -P120 - P180 - P240
Cleaning:	Fresh product can be cleaned with acetone, alcohol or universal solvent. Once hardened, remove mechanically.
Safety:	Read the label and the Safety Data Sheet before using the product. Comply with current safety, occupational hygiene and waste management regulations.
Storage	Store in its original, tightly closed container in a cool, dry, ventilated place, protected from moisture and direct sunlight, between +5 °C and +30 °C.
Shelf life:	3 years in its original unopened container.

230726

FEATURES

- 2K polyester filler.
- Ultralight, low-density formula.
- Ideal when the weight of the repair needs to be minimised.
- Creamy formula, easy to work with.
- Easy and fast to apply.
- Ideal for working on large surfaces.
- Fast drying.
- Easy to sand.
- Good filling capacity.
- White colour.

APPLICATIONS

Ideal for:

- Filling and levelling of large surfaces.
- Repair of car bodies and automotive parts.
- Repair of fibreglass surfaces.
- Repair of parts where added weight must be reduced.
- Restoration and maintenance work.
- Professional repairs requiring fast, easy application.

Its excellent workability and low density make it especially suitable for large-surface repairs, where a conventional filler could add unnecessary weight and require greater effort to apply and sand.

IMAGEN



LABELS

