

Product Information | TECHNICAL DATA SHEET

UNIVERSAL FILLER

250g / 8,82 oz - 500 g / 17,64 oz

GENERAL DESCRIPTION

Styrene-free, two-component polyester filler developed to provide strong and durable repairs easily, quickly, and reliably. It is the ideal all-purpose filler when you are looking for a single, reliable solution for your repair needs. Its excellent adhesion and versatility make it a practical solution for a wide variety of repair, filling, and leveling applications. Its creamy formula facilitates application with a spatula, even on vertical surfaces, while its good filling capacity allows dents, irregularities, cracks, and damage to be corrected. It also hardens quickly, is easy to sand, and can be overpainted with any type of paint.

INSTRUCTIONS FOR USE

- Prepare the surface so that it is dry, clean, and free of dust, grease, dirt, rust, and poorly adhered paint.
- Pre-sand the substrate with P60-P80 sandpaper to promote adhesion.
- On rusty surfaces, completely remove the rust and subsequently apply MTN WEPRO Grey or Red Anti-Corrosion Primer.
- Apply a line of catalyst across the entire portion of filler (100:2 ratio). Mix thoroughly until a homogeneous mixture with uniform color is obtained.
- For greater thicknesses, apply in several layers, allowing each layer to harden completely before applying the next.
- Allow to dry for 30 min at a temperature of 20°C. Drying time will depend on the ambient temperature. Higher temperatures accelerate curing.
- Initially sand with P80-P120 sandpaper and continue with P180-P240 for finishing. For high-quality finishes, use finer grades.
- Antes del acabado final comprobar que la reparación está completamente endurecida.
- It is recommended to apply a coat of MTN WEPRO Grey Insulating Primer before the final finish and sand it with P600/P800.
- Clean spatulas with MTN WEPRO Cleaning Solvent or universal cleaning solvent before the product hardens.

PHYSICAL CHARACTERISTICS

Colour:	Grey
Nature:	Styrene-free unsaturated polyester
Specific gravity:	1.6 kg/L at 20°C
VOC:	222 g/L
Working time once mixed with catalyst:	3 min at 30°C 5 min at 20°C 11 min at 10°C
Drying time:	15-20 min at 30°C 20- 25 min at 20°C 30-40 min at 10°C
Complete curing:	Approximately 2 hours (20°C)
Recommended sanding:	Initial: P80 - P120 - P180 Finish: P240 or higher, depending on the desired finish
Safety:	Consult the label and Safety Data Sheet before using the product. Comply with applicable safety, occupational hygiene, and waste-management regulations.
Cleaning:	Fresh product can be cleaned with acetone, alcohol, or universal solvent. Once hardened, remove mechanically.
Storage:	Keep in the original, tightly closed container in a cool, dry, well-ventilated place, protected from moisture and direct sunlight, between +5°C and +30°C.
Shelf life:	3 years in the original unopened container.

230726

FEATURES

- Styrene-free.
- 2K polyester filler.
- Good adhesion to multiple surfaces.
- Suitable for steel, galvanized steel, cast iron, and fiberglass.
- Ideal for repairs, filling, and leveling.
- Good filling capacity.
- Creamy, easy-to-apply formula.
- Easy to sand.
- Fast and durable repairs.
- Can be overpainted with any type of paint.
- Grey color.
- Ideal for automotive, industrial, and DIY applications.

APPLICATIONS

All-purpose solution for repairs, filling, and leveling work, providing fast, simple, and reliable results.

Can be applied to:

- Repairing dents and damage.
- Filling cracks, irregularities, and damaged areas.
- Leveling surfaces before painting.
- Automotive bodywork repair and preparation.
- Repairing metal parts.
- Repairing fiberglass components.
- Industrial maintenance and repair work.
- DIY and restoration projects.

Puede aplicarse sobre:

- Steel
- Galvanized steel
- Cast iron
- Fiberglass
- Wood
- Most plastics

Once hardened and sanded, the repaired surface can be repainted with any type of paint.

IMAGE



Dimensions:

250 g: Height 92 mm, diameter 75 mm 500 g: Height 130 mm, diameter 99 mm

LABELS

 COD. BARRAS/BAR CODE	Masilla Universal / Universal Filler 250 g SPMA0101001
	Masilla Universal / Universal Filler 500 g SPMA0101007